

HMIS RATING	
Health	1
Flammability	4
Reactivity	3

MATERIAL SAFETY DATA SHEET

NFPA 704 RATING	
Health	1
Flammability	4
Reactivity	3
NFPA 30B LEVEL	
3	

KIMBALL-MIDWEST
P.O. BOX 2470
COLUMBUS, OH 43216-2470

CORPORATE & EMERGENCY TELEPHONE: 800-424-9300

1 PRODUCT IDENTIFICATION

PART NUMBER.....80-633
PRODUCT NAME.....ULTRA PRO-MAX GRAY ANSI 61PAINT 16 OZ.
AEROSOL CAN
CHEMICAL FAMILY.....N/A
DOT SHIPPING.....Limited Quantity (LQ)

2 HAZARDOUS INGREDIENTS

SPECIFIC CHEMICAL IDENTITY, COMMON NAMES	OSHA PEL	REL	TLV	%
Acetone (00067-64-1)	1000ppm	250ppm	750ppm	18.03
Propane (00074-98-6)	1000ppm	1000ppm	2500ppm	15.82
N-Butane (00106-97-8)	-	800ppm	800ppm	9.29
Calcium carbonate (1317-65-3)				8.18
Titanium Dioxide (13463-67-7)	-	-	-	6.89
*Glycol Ether EP (02807-30-9)	-	-	-	4.87
*Methyl Iso-butyl Ketone (00108-10-1)	100ppm	75ppm	75ppm	4.6
Isobutyl acetate (110-19-0)	150ppm	150ppm	150ppm	3.49
Methyl Propyl Ketone (00107-87-9)	200ppm	150ppm	250ppm	3.05
*Xylene (01330-20-7)	100ppm	150ppm	150ppm	2.41
PM acetate (108-65-6)	-	-	-	1.69

All chemical compounds marked with an asterisk (*) are toxic chemicals subject to the reporting of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372. You must notify each person to whom this mixture of trade name product is sold. This statement must not be detached. Any copy or redistribution of this Material Safety Data Sheet shall include this statement. (+=Non-Hazardous Component)

3 PHYSICAL DATA

BOILING POINT (RANGE).....-44°C (-47°F)
VAPOR PRESSURE PSIG @ 68°F.....2750 hPa
VAPOR DENSITY (AIR = 1).....N/A
SOLUBILITY IN WATER.....Slight
SPECIFIC GRAVITY (H₂O = 1).....Between 0.77 and 0.85
MELTING/FREEZING POINT.....N/A
EVAPORATION RATE (Ether=1).....>1
VOC content (by weight).....46.6%, 496.6g/L
APPEARANCE AND ODOR.....Gray liquid/Aromatic

4 FIRE AND EXPLOSION DATA

FLASH POINT.....-19°C (-2°F)
UPPER EXPLOSIVE LIMIT (%).....10.9%
LOWER EXPLOSIVE LIMIT (%).....1.7%
EXTINGUISHING MEDIA.....Extinguishing powder, CO₂, Sand. Do not use water!
SPECIAL FIREFIGHTING
PROCEDURES.....Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.
FIRE AND EXPLOSION HAZARDS.....Vapors may form explosive mixture with air.
NFPA Flammability Hazard.....4

5 HFAITH FFFFCTS DATA

SHORT TERM EFFECTS OF EXPOSURE

ROUTE OF ENTRY.....Skin absorption, Inhalation, Ingestion, Eye contact, Skin contact
HEALTH HAZARDS
(ACUTE AND CHRONIC).....Extremely flammable. Irritating to eyes and respiratory system. Vapors may cause drowsiness and dizziness. May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE.....Heart disease, respiratory disorders.

5 HFAITH FFFFCTS DATA (CONT'D)

FIRST AID PROCEDURES

EYE CONTACT.....Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.
SKIN CONTACT.....Wash with soap and water. Get medical attention if irritation develops or persists.
INHALATION.....Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Rescuers should put on appropriate protective gear. Keep victim warm. Get immediate medical attention.
INGESTION.....If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SPECIAL HEALTH EFFECTS

CARCINOGEN (OSHA Guidelines).....This product contains chemicals known to the State of California to cause cancer.

6 REACTIVITY

STABILITY	Stable under normal conditions.
INCOMPATIBILITIES	No dangerous reactions known.
HAZARDOUS DECOMPOSITION	No decomposition if used according to specifications.
PRODUCTS	May produce hazardous fumes when heated to decomposition. Fumes may contain CO ₂ , CO.
HAZARDOUS POLYMERIZATION	Will not occur under normal conditions.
HAZARDOUS POLYMERIZATION CONDITIONS..	None known.

7 PRFCAUTIONS FOR SAFF HANDLING & USE

PROTECTIVE EQUIPMENT REQUIREMENTS	Safety goggles. Local exhaust ventilation may be necessary to control air contaminants to within TLVs during the use of this product. Wash with soap and water.
WASH REQUIREMENTS SPILL OR LEAK PROCEDURES	Absorb spill with inert material (e.g. dry sand or earth), then place in chemical waste container.
WASTE DISPOSAL METHODS	Dispose in accordance with local, state, and federal regulations.
HANDLING & STORAGE	Wash thoroughly after handling. Keep away from heat, sparks, and flames. Store below 120°F.
OTHER PRECAUTIONS	Use NIOSH approved respirator with an organic vapor cartridge; avoid prolonged breathing of vapors; protection provided by air purifying respirators is limited.

8 ADDITIONAL INFORMATION

Use self-contained breathing apparatus if TLV limits are exceeded. Do not eat or smoke while using. Wash hands after use. Use positive pressure air supplied respirator if there is potential for uncontrolled release, if exposure levels are unknown, or in any circumstance where air purifying respirators may not provide adequate protection.

THE INFORMATION GIVEN AND THE RECOMMENDATIONS MADE HEREIN APPLY TO OUR PRODUCT(S) ALONE AND ARE NOT COMBINED WITH OTHER PRODUCTS. SUCH INFORMATION IS BASED UPON OUR RESEARCH AND ON DATA FROM OTHER RELIABLE SOURCES AND IS BELIEVED TO BE ACCURATE. NO GUARANTEE OF ACCURACY IS MADE. IT IS THE PURCHASER'S RESPONSIBILITY BEFORE USING ANY PRODUCT TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS AND TO DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PURPOSES.

**KIMBALL
MIDWEST**

Specializing in Materials Management since 1923