

A00393 MG 41 PENETRATING OIL 16N12 (WWIP)

Version 1.0

Revision Date 02/12/2015

Print Date 07/31/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : A00393 MG 41 PENETRATING OIL 16N12 (WWIP)

Material number : 00000000001006964

Manufacturer or supplier's details

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW
Atlanta, GA 30318

Telephone : 404-352-1680

Emergency telephone numbers
For SDS Information : Compliance Services 1-877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616

SECTION 2. HAZARDS IDENTIFICATION
Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	opaque, light brown
Odour	solvent-like

GHS Classification

 Flammable aerosols : Category 1
 Gases under pressure : Liquefied gas
 Skin irritation : Category 2
 Eye irritation : Category 2A

GHS Label element

Hazard pictograms :



Signal word : Danger

 Hazard statements : H222 Extremely flammable aerosol.
 H280 Contains gas under pressure; may explode if heated.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.

 Precautionary statements : **Prevention:**
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Pressurized container: Do not pierce or burn, even after

A00393 MG 41 PENETRATING OIL 16N12 (WWIP)

Version 1.0

Revision Date 02/12/2015

Print Date 07/31/2015

use.

P264 Wash skin thoroughly after handling.

P280 Wear eye protection/ face protection.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Potential Health Effects**Carcinogenicity:****IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Hazardous components**

Chemical Name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light (Vapour and gas)	64742-47-8	>= 50 - < 70
Stoddard solvent	8052-41-3	>= 20 - < 30
propane	74-98-6	>= 5 - < 10
butane	106-97-8	>= 5 - < 10
1,2,4-trimethylbenzene	95-63-6	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice : Show this safety data sheet to the doctor in attendance.
Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

A00393 MG 41 PENETRATING OIL 16N12 (WWIP)

Version 1.0

Revision Date 02/12/2015

Print Date 07/31/2015

- If inhaled : If inhaled, remove to fresh air.
Consult a physician after significant exposure.
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : Remove contaminated clothing and shoes.
Wash clothing before reuse.
Wash off immediately with plenty of water for at least 15 minutes.
Call a physician if irritation develops or persists.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
If in eyes, rinse with water for 15 minutes.
- If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
If symptoms persist, call a physician.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Fluorine compounds
- Specific extinguishing methods :
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

A00393 MG 41 PENETRATING OIL 16N12 (WWIP)

Version 1.0

Revision Date 02/12/2015

Print Date 07/31/2015

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Keep people away from and upwind of spill/leak.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Sweep up or vacuum up spillage and collect in suitable container for disposal.
-

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
No smoking.
Observe label precautions.
Keep in a dry place.
Electrical installations / working materials must comply with the technological safety standards.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Materials to avoid : Oxidizing agents
Do not freeze.
- Storage temperature : < 49 °C
-

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A00393 MG 41 PENETRATING OIL 16N12 (WWIP)

Version 1.0

Revision Date 02/12/2015

Print Date 07/31/2015

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m ³	NIOSH REL
		C	1,800 mg/m ³	NIOSH REL
		TWA	500 ppm 2,900 mg/m ³	OSHA Z-1
propane	74-98-6	TWA	100 ppm 525 mg/m ³	OSHA P0
		TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m ³	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m ³	OSHA Z-1
butane	106-97-8	TWA	1,000 ppm 1,800 mg/m ³	OSHA P0
		TWA	800 ppm 1,900 mg/m ³	NIOSH REL
		TWA	800 ppm 1,900 mg/m ³	OSHA P0
		TWA	25 ppm 125 mg/m ³	NIOSH REL
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m ³	NIOSH REL

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Safety glasses

Skin and body protection : impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : opaque, light brown

Odour : solvent-like

A00393 MG 41 PENETRATING OIL 16N12 (WWIP)

Version 1.0

Revision Date 02/12/2015

Print Date 07/31/2015

Odour Threshold	: no data available
pH	: not applicable
Melting point/freezing point	: no data available
Boiling point	: no data available
Flash point	: not applicable
Evaporation rate	: no data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Relative vapour density	: no data available
Density	: 0.810 g/cm ³
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: not determined
Thermal decomposition	: no data available
Viscosity	
Viscosity, kinematic	: no data available
Heat of combustion	: 47.28 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon oxides

A00393 MG 41 PENETRATING OIL 16N12 (WWIP)

Version 1.0

Revision Date 02/12/2015

Print Date 07/31/2015

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

Acute inhalation toxicity : Acute toxicity estimate : > 10 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Skin corrosion/irritation**Product:**

Remarks: Irritating to skin.

Serious eye damage/eye irritation**Product:**

Remarks: Severe eye irritation

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

Distillates (petroleum), hydrotreated light (Vapour and gas):

Stoddard solvent:

propane:

butane:

1,2,4-trimethylbenzene:

STOT - single exposure

no data available

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

Further information**Product:**

Remarks: no data available

Components:

A00393 MG 41 PENETRATING OIL 16N12 (WWIP)

Version 1.0

Revision Date 02/12/2015

Print Date 07/31/2015

Distillates (petroleum), hydrotreated light (Vapour and gas):
 Remarks: no data available

SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity

no data available

Persistence and degradability

no data available

Bioaccumulative potential
Product:

Partition coefficient: n-
 octanol/water : Remarks: no data available

Components:

butane :
 Partition coefficient: n-
 octanol/water : Pow: 2.89

Mobility in soil

no data available

Other adverse effects

no data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of
 Stratospheric Ozone - CAA Section 602 Class I
 Substances

Remarks This product neither contains, nor was manufactured
 with a Class I or Class II ODS as defined by the U.S.
 Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A
 + B).

Additional ecological : An environmental hazard cannot be excluded in the
 information event of unprofessional handling or disposal., Toxic to
 aquatic life with long lasting effects.

Components:

Distillates (petroleum), hydrotreated light (Vapour and gas) :

Additional ecological : no data available
 information

SECTION 13. DISPOSAL CONSIDERATIONS
Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

A00393 MG 41 PENETRATING OIL 16N12 (WWIP)

Version 1.0

Revision Date 02/12/2015

Print Date 07/31/2015

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Do not re-use empty containers.
 Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):
 ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):
 UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):
 UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):
 UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):
 UN1950, AEROSOLS, 2.1, - Limited quantity

SECTION 15. REGULATORY INFORMATION
EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylenes	1330-20-7	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard
 Fire Hazard
 Sudden Release of Pressure Hazard

SARA 302 : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

A00393 MG 41 PENETRATING OIL 16N12 (WWIP)

Version 1.0

Revision Date 02/12/2015

Print Date 07/31/2015

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

1,2,4-trimethylbenzene	95-63-6	1.2095 %
------------------------	---------	----------


California Prop 65 This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA	On TSCA Inventory
DSL	This product contains one or several components that are not on the Canadian DSL nor NDSL.
AICS	Not in compliance with the inventory
NZIoC	Not in compliance with the inventory
PICCS	Not in compliance with the inventory
IECSC	Not in compliance with the inventory

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION
Further information
NFPA:

HMIS III:

HEALTH	3
FLAMMABILITY	4
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA GHS Label Information:

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation.

Precautionary statements

: **Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source.

A00393 MG 41 PENETRATING OIL 16N12 (WWIP)

Version 1.0

Revision Date 02/12/2015

Print Date 07/31/2015

Pressurized container: Do not pierce or burn, even after use. Wash skin thoroughly after handling. Wear eye protection/ face protection. Wear protective gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.