




MATERIAL SAFETY DATA SHEET

This form complies with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. The information contained herein is believed to be accurate but is not warranted for accuracy whether originating with this company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

NFPA SYMBOL



4 Extreme
3 High
2 Moderate
1 Slight
0 Insignificant

IDENTITY: (AS USED ON LABEL AND LIST)

Foremost 1337-ES Rust Ban (Aerosol)

FOR CHEMICAL EMERGENCY CALL: INFOTRAC 1-800-535-5053

SECTION I

ADDRESS:

Delta Foremost Chemical Corporation
3915 Air Park St.
Memphis, Tennessee 38118

EMERGENCY TELEPHONE NUMBER: INFOTRAC

TELEPHONE NUMBER FOR INFORMATION: (901) 363-4340

DATE PREPARED: January 05, 2016

SECTION II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS SPECIFIC CHEMICAL IDENTITY: COMMON NAME(s)

	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	% (OPTIONAL)
CAS# 142-82-5 Heptane	50 ppm	50 ppm	N/L	N/L
CAS# 8052-41-3 Mineral Spirits	500 ppm	500 ppm	N/L	N/L
CAS# 74-98-6 propane	1000 ppm	1000 ppm	N/L	N/L
CAS# 106-97-8 N-butane	600 ppm	600 ppm	N/L	N/L

SECTION III: PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: N/A

SPECIFIC GRAVITY: (WATER = 1) 0.78

VAPOR PRESSURE: (mm Hg.) not est.

MELTING POINT: N/A

VAPOR DENSITY: (AIR = 1) not est.

EVAPORATION RATE: (BUTYL ACETATE = 1) not est.

SOLUBILITY IN WATER: Insoluble

APPEARANCE AND ODOR: Fine brown spray with solvent odor

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: (METHOD USED) 0°F TCC

FLAMMABLE LIMITS: LEL: N/A

UEL: N/A

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, or foam is recommended.

SPECIAL FIRE FIGHTING PROCEDURES: EXTREMELY FLAMMABLE. Contents under pressure. Cool exposed containers with water spray to prevent bursting. SCBA should be used whenever chemical fires are present.

UNUSUAL FIRE AND EXPLOSION HAZARD: None known.

SECTION V: REACTIVITY DATA

REACTIVITY: Stable

CONDITIONS TO AVOID: Heat, sparks, and open flame.

INCOMPATIBILITY: (MATERIALS TO AVOID) Acids and strong oxidizers.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Carbon monoxide and carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID: None

SECTION VI: HEALTH HAZARD DATA

ROUTE(S) OF ENTRY:

INHALATION: Yes

SKIN: Yes

INGESTION: Yes

HEALTH HAZARDS: (ACUTE AND CHRONIC) EYES: May cause mild eye irritation. Symptoms include stinging, tearing and redness. SKIN: May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying of skin and skin burns. INHALATION: High vapor/ aerosol concentrations (>1000 ppm) are irritating to the eyes and respiratory tract. May cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death. May cause peripheral nervous system disorder and/or damage. INGESTION: Harmful or fatal if swallowed. Aspiration hazard – this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

CARCINOGENICITY:

NTP: No

IARC MONOGRAPHS: No

OSHA REGULATED: No

SIGNS AND SYMPTOMS OF EXPOSURE: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness)

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None

EMERGENCY AND FIRST AID PROCEDURES: EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. SKIN: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Get medical attention immediately. INHALATION: Remove victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. INGESTION: Seek medical attention immediately. Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Do not leave individual unattended.

SECTION VII: PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Eliminate all ignition sources. Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not use or store near heat, sparks or open flame. Exposure to temperatures above 120°F may cause bursting. Do not puncture or incinerate container. Store in a cool, dry place. Do not get in eyes, on skin, or on clothing. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal. Keep out of reach of children.

OTHER PRECAUTIONS: None

SECTION VIII: CONTROL MEASURES

RESPIRATORY PROTECTION: (SPECIFY TYPE) Self-contained breathing apparatus if above TLV limit.

VENTILATION: LOCAL EXHAUST: Normal

SPECIAL: None

MECHANICAL: (GENERAL) Normal

OTHER: None

PROTECTIVE GLOVES: Rubber or neoprene

EYE PROTECTION: Goggles or safety glasses

WORK/HYGIENIC PRACTICES: Use normal industrial hygiene practices.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None