

ITEM: 4X543 - Sealant Tape 1/2 In. W 520 In. L

MSDS: A9906

ORDER: 0141391392

LP NUMBER: U862719675

MATERIAL SAFETY DATA SHEET (MSDS)

This MSDS should be attached or kept with the respective product with which it is associated.

MATERIAL SAFETY DATA SHEET - A9906

Associated Grainger Items
4UJ93, 4UK05, 4UK06, 4UK07, 4X227, 4X543, 4X773, 5X584, 5X585, 5X720

MATERIAL SAFETY DATA SHEET

A
ANTI-SEIZE TECHNOLOGY

A.S.T. INDUSTRIES, INC.

POLY-TEMP (R*) GAS

YELLOW GAS LINE PIPE TAPE

STOCK#: 46330, 46330A, 46335, 46335A, 46340, 46345, 46350, 46350A

H.M.I.S.:
H 1
F 0
R 0
P.P. A

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURE:
ANTI-SEIZE TECHNOLOGY
2345 N. 17TH AVE.
FRANKLIN PARK, IL 60131

PHONE: 847-455-2300

EMERGENCY PHONE, 24 HR:
INFOTRAC @: 1-800-535-5053 OR 352-323-3500

SECTION 2 - COMPOSITION/ INFORMATION ON INGREDIENTS

	CAS #	OSHA PEL	TLV	PERCENT
POLYTETRAFLUROETHYLENE (99.9% VIRGIN MATERIAL)	9002-84-0	NOT ESTABLISHED	100	

SECTION 3 - HAZARD IDENTIFICATION

ROUTES OF ENTRY:
 SKIN
 EYES
 INHALATION
 INGESTION

HEALTH HAZARDS:
"PTFE (A.K.A. TEFLON) IS RELATIVELY NON-TOXIC. THE PRIMARY HEALTH HAZARD ASSOCIATED WITH "PTFE" IS EXTREMELY HIGH TEMPERATURE THERMAL DECOMPOSITION BY PRODUCTS. DO NOT USE THIS PRODUCT IN APPLICATIONS WHERE THE TEMPERATURE IS EXPECTED TO EXCEED 550F AT TEMPERATURES EXCEEDING 572 F, PARTICULATE MATTER CAN FORM WHICH COULD RESULT IN A CONDITION KNOWN AS "POLYMER FUME FEVER", A TEMPORARY FLU-LIKE CONDITION WITH CHILLS, FEVER, NAUSEA MUSCLE OR JOINT ACHE AND SOMETIMES COUGH. THIS CAN OCCUR IF TOBACCO PRODUCTS ARE CONTAMINATED WITH PTFE PARTICLES WHICH IS UNLIKELY WITH THIS PRODUCT. OTHER TOXIC AND CORROSIVE FUMES MAY BE EVOLVED."

SECTION 4 - FIRST AID MEASURES

SKIN: WASH WITH SOAP AND WATER.

EYES: UNLIKELY

INGESTION:
IF INGESTED THIS PRODUCT IS NOT EXPECTED TO CAUSE AN ACUTE REACTION. CALL A POISON CONTROL CENTER OR A PHYSICIAN.

INHALATION:
NOT LIKELY UNDER NORMAL CONDITIONS OF USE. IF USING IN HIGH TEMPERATURE APPLICATIONS WHERE THERMAL DECOMPOSITION IS LIKELY, USE A LOCAL EXHAUST TO REMOVE FUMES. IF DIZZINESS OR IRRITATION OCCURS, SEEK FRESH AIR.

CHEMICAL ('S) LISTED AS CARCINOGENS:
NTP?: NO
I.A.R.C.? NO
OSHA?: NO

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT AND METHOD USED: DOES NOT APPLY. DOES NOT BURN

FLAMMABLE LIMITS:
LEL: NO DATA
UEL: NO DATA

EXTINGUISHING MEDIA: FOAM, CO₂, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: MAY EMIT TOXIC FUMES IN A FIRE

UNUSUAL FIRE AND EXPLOSION HAZARDS:
DENSE SMOKE AND NOXIOUS OR TOXIC FUMES MAY BE GENERATED IN A FIRE. FIRE FIGHTERS SHOULD WEAR A SELF-CONTAINED BREATHING APPARATUS.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:
SUPPLIED AS A SOLID TAPE LIKE MATERIAL. DOES NOT APPLY

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: NONE REASONABLY FORESEEN.

OTHER PRECAUTIONS: KEEP AWAY FROM CHILDREN.

SPILL / LEAKAGE PROCEDURES: DOES NOT APPLY

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION:

NORMALLY NOT REQUIRED. IF THIS PRODUCT IS BEING USED IN HIGH TEMPERATURE APPLICATIONS WHERE THE PRODUCT "SMOKES", USE A LOCAL EXHAUST OR VENTILATE THE AREA TO MAINTAIN THE AIR QUALITY. A "N.I.O.S.H." APPROVED ORGANIC VAPOR RESPIRATOR IS ALSO ACCEPTABLE.

PROTECTIVE GLOVES: NOT REQUIRED.

EYE PROTECTION: NOT REQUIRED.

WORK/HYGIENIC PRACTICES:
USE GOOD STANDARD PRACTICES WHEN USING THIS MATERIAL. DO NOT SMOKE WHILE USING.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: DOES NOT APPLY

SOLUBILITY IN WATER: NONE

MELTING POINT: OVER 500 F

REACTIVITY IN WATER: NONE

VAPOR PRESSURE: 0

SPECIFIC GRAVITY: 0.35 - 1.5 DEPENDING ON GRADE OF TAPE

EVAPORATION RATE: 0

PERCENT VOLATILE: 0

APPEARANCE AND ODOR: WHITE PLASTIC LIKE TAPE, NO ODOR

SECTION 10 - STABILITY AND REACTIVITY

STABILITY:

STABLE
 UNSTABLE

CONDITIONS TO AVOID: TEMPERATURE OVER 500F

INCOMPATABILITY, (MATERIALS TO AVOID):
FLUORINE AND RELATED COMPOUNDS, CHLORINE TRIFLUORIDE, ALKALI METALS, INTERHALOGEN COMPOUNDS.

HAZARDOUS DECOMPOSITION PRODUCTS:

IF THE SERVICE TEMPERATURES EXCEEDS 750 F. THEN "PTFE" WILL BEGIN TO UNDERGO THERMAL DECOMPOSITION. AT THESE TEMPERATURES "PTFE" CAN EMIT ACUTELY TOXIC VAPORS. THESE VAPORS CAN INCLUDE HEXAFLUOROPROPYLENE, PERFLUOROCARBONYL FLUORIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION 11 - TOXICOLOGICAL INFORMATION

LD50: NOT DATA

LC50: NOT DATA

PTFE (A.K.A. "TEFLON") IS NOT CONSIDERED TOXIC

SECTION 12 - ECOLOGICAL INFORMATION

NOT EXPECTED TO POSE ANY HAZARDS

SECTION 13 - DISPOSAL CONSIDERATION

WASTE DISPOSAL:

DISPOSE OF IN A RESPONSIBLE MANNER. FOLLOW LOCAL, STATE AND FEDERAL GUIDELINES. INCINERATION IS THE PREFERRED METHOD OF DISPOSAL, ALTHOUGH IT MAY BE LANDILLED AT AN APPROVED FACILITY.

SECTION 14 - TRANSPORT INFORMATION

TRANSPORTATION BY LAND (49 CFR): NOT REGULATED

TRANSPORTATION BY AIR (ICAO/IATA): NOT REGULATED

TRANSPORTATION BY SHIP (IMO/IMDG): NOT REGULATED

SECTION 15 - REGULATORY INFORMATION

CALIFORNIA PROPOSITION 65: NO

RCRA: NO

OZONE DEPLETING SUBSTANCES: NONE

DOT SHIPPING CLASS: NOT HAZARDOUS

SARA TITLE III: NO

TASCA INVENTORY: ALL INGREDIENTS LISTED

CERCLA: NO

NFPA RATING:

H 2

F 1

R 0

SECTION 16 - OTHER INFORMATION

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS OBTAINED FROM THE USE OF HIS PRODUCT. THEREFORE, BECAUSE THE PRODUCT MAY BE USED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO LIABILITY FOR ITS USE.

DATE: 01/15/2009

POLY TEMP GAS TAPE, 16 PART ISO MSDS