



Univar USA Inc Material Safety Data Sheet

MSDS No:

Version No:

Order No:

Univar USA Inc., 17425 NE Union Hill Rd., Redmond WA 98052
(425) 889 3400

Emergency Assistance

For emergency assistance involving chemicals call
Chemtrec - (800) 424-9300

The Version Date and Number for this MSDS is : 02/27/2009 - #021

PRODUCT NAME: CAUSTIC SODA LIQUID (ALL GRADES)

MSDS NUMBER: OZ32415

DATE ISSUED: 01/07/2009

SUPERSEDES: 11/12/2008

ISSUED BY: 008730

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Distributed by:

Univar USA Inc.

17425 NE Union Hill Rd.

Redmond, WA 98052

425-889-3400

Trade Name:

Caustic Soda Diaphragm Grade 10%, 15%, 18%, 20%, 25%, 30%, 35%, 40%, 50%,
Caustic Soda Rayon Grade 18%, 20%, 25%, 30%, 50%, 50% Caustic Soda Rayon
Grade OS, Caustic Soda Membrane 6%, 18%, 20%, 25%, 30%, 48%, 50%, 50% Caustic
Soda Membrane OS, 50% Caustic Soda Diaphragm OS, Caustic Soda Low Salt 50%,
25% Caustic Soda Purified, 50% Caustic Soda Purified, 50% Caustic Soda
Purified OS, Caustic Soda Liquid 70/30, Membrane Blended, 50% Caustic Soda
Membrane (Northeast), 50% Caustic Soda Diaphragm (West Coast), 50% Blended
Rayon Grade Blended, Membrane Cell Liquor

Synonyms: Sodium hydroxide solution, Liquid Caustic, Lye Solution, Caustic,
Lye, Soda Lye

Product Use: Metal finishing, Cleaner, Process chemical, Petroleum industry

2. HAZARDS IDENTIFICATION EMERGENCY OVERVIEW:

Color: Colorless to slightly colored

Physical State: Liquid

Odor: Odorless

Signal Word: Danger

MAJOR HEALTH HAZARDS: CORROSIVE. CAUSES BURNS TO THE RESPIRATORY TRACT, SKIN,
EYES AND GASTROINTESTINAL TRACT. CAUSES PERMANENT EYE DAMAGE.

PHYSICAL HAZARDS: CORROSIVE. Mixing with water, acid or incompatible materials may cause splattering and release of heat.

ECOLOGICAL HAZARDS: Keep out of water supplies and sewers. This material is alkaline and may raise the pH of surface waters. This material has exhibited moderate toxicity to aquatic organisms.

PRECAUTIONARY STATEMENTS: Avoid breathing vapors or mist. Avoid contact with skin, eyes and clothing. Keep container tightly closed. Wash thoroughly after handling. Use only with adequate ventilation.

POTENTIAL HEALTH EFFECTS:

Inhalation: May cause irritation (possibly severe), chemical burns, and pulmonary edema.

Skin contact: May cause irritation (possibly severe) and chemical burns.

Eye contact: May cause irritation (possibly severe), chemical burns, eye damage, and blindness.

Ingestion: May cause irritation (possibly severe), chemical burns, nausea, and vomiting.

Target Organs Effected: Respiratory System, Skin, Eye

Medical Conditions Aggravated by Exposure: Asthma, Respiratory disorders

See Section 11: TOXICOLOGICAL INFORMATION

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Component	Concentration (by weight %)	CAS - No.
Water	48.5 - 94.5	7732-18-5
Sodium hydroxide	5.5 - 51.5	1310-73-2
Sodium chloride (NaCl)	1 - 5	7647-14-5

4. FIRST AID MEASURES

Inhalation: If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. If respiration or pulse has stopped, have a trained person administer basic life support (Cardio-Pulmonary Resuscitation/Automatic External Defibrillator) and CALL FOR EMERGENCY SERVICES IMMEDIATELY.

Skin Contact: Immediately flush contaminated areas with water. Remove contaminated clothing, jewelry, and shoes immediately. Wash contaminated areas with soap and water. Thoroughly clean and dry contaminated clothing before reuse. Discard contaminated leather goods. GET MEDICAL ATTENTION

IMMEDIATELY.

Eye Contact: Immediately flush eyes with a directed stream of water for at least 15 minutes, forcibly holding eyelids apart to ensure complete irrigation of all eye and lid tissues. Washing eyes within several seconds is essential to achieve maximum effectiveness. GET MEDICAL ATTENTION IMMEDIATELY.

Ingestion: Never give anything by mouth to an unconscious or convulsive person. If swallowed, do not induce vomiting. Give large amounts of water. If vomiting occurs spontaneously, keep airway clear. Give more water when vomiting stops. GET MEDICAL ATTENTION IMMEDIATELY.

Notes to Physician: The absence of visible signs or symptoms of burns does NOT reliably exclude the presence of actual tissue damage. Probable mucosal damage may contraindicate the use of gastric lavage.

5. FIRE-FIGHTING MEASURES

Fire Hazard: Negligible fire hazard.

Extinguishing Media: Use media appropriate for surrounding fire

Fire Fighting: Move container from fire area if it can be done without risk. Cool containers with water. Avoid contact with skin.

Sensitivity to Mechanical Impact: Not sensitive.

Sensitivity to Static Discharge: Not sensitive.

Flash point: Not flammable

6. ACCIDENTAL RELEASE MEASURES

Occupational Release:

Wear appropriate personal protective equipment recommended in Section 8 of the MSDS. Completely contain spilled material with dikes, sandbags, etc. Shovel dry material into suitable container. Liquid material may be removed with a vacuum truck. Remaining material may be diluted with water and neutralized with dilute acid, then absorbed and collected. Flush spill area with water, if appropriate. Keep product and flush water out of water supplies and sewers. This material is alkaline and may raise the pH of surface waters with low buffering capacity. Releases should be reported, if required, to appropriate agencies.

7. HANDLING AND STORAGE

Storage Conditions: Store and handle in accordance with all current regulations and standards. Keep container tightly closed and properly labeled. Do not store in aluminum container or use aluminum fittings or transfer lines, as flammable hydrogen gas may be generated. Keep separated

from incompatible substances.

Handling Procedures: Avoid breathing vapor or mist. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. When mixing, slowly add to water to minimize heat generation and spattering.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

OSHA Regulatory Exposure limit(s) :

Hazardous						
Component	CAS-No.	OSHA Final PEL	OSHA Final PEL	OSHA Final PEL		
		TWA	STEL		Ceiling	
Sodium hydroxide	1310-73-2	2 mg/m ³				

Non-Regulatory Exposure Limit(s) :

The Non-Regulatory OSHA limits shown in the table are the Vacated 1989 PEL's (vacated by 58 FR 35338, June 30, 1993).

Hazardous						
Component	CAS-No.	ACGIH	ACGIH	ACGIH	OSHA	OSHA Ceiling
		TWA	STEL	Ceiling	TWA	STEL (Vacated)
Sodium hydroxide	1310-73-2			2 mg/m ³		2 mg/m ³

ENGINEERING CONTROLS: Provide local exhaust ventilation where dust or mist may be generated. Ensure compliance with applicable exposure limits.

PERSONAL PROTECTIVE EQUIPMENT:

Eye Protection: Wear chemical safety goggles with a faceshield to protect against eye and skin contact when appropriate. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin and Body Protection: Wear chemical resistant clothing and rubber boots when potential for contact with the material exists. Contaminated clothing should be removed, then discarded or laundered.

Hand Protection: Wear appropriate chemical resistant gloves Protective Material Types: Natural rubber, Neoprene, Nitrile

Hazardous Component	Immediately Dangerous to Life/ Health (IDLH)
Sodium hydroxide	10 mg/m ³ IDLH

Respiratory Protection: A NIOSH approved respirator with N95 (dust, fume, mist) cartridges may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits, or when symptoms have been observed that are indicative of overexposure. If eye

irritation occurs, a full face style mask should be used. A respiratory protection program that meets 29 CFR 1910.134 must be followed whenever workplace conditions warrant use of a respirator.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid
Appearance: Clear to opaque
Color: Colorless to slightly colored
Odor: Odorless
Boiling Point/Range: 230 - 291 F (110 - 144 C)
Freezing Point/Range: -26 to 59 F (-32 to 15 C)
Vapor Pressure: 13 - 135 mmHg @ 60 C
Vapor Density (air=1): No data available
Specific Gravity (water=1): 1.11 - 1.53 @ 15.6 C
Water Solubility: 100%
pH: 14.0 (7.5% solution)
Volatility: No data available
Evaporation Rate (ether=1): No data available
Partition Coefficient (n-octanol/water): No data available

10. STABILITY AND REACTIVITY

Reactivity/ Stability: Stable at normal temperatures and pressures.

Conditions to Avoid: Mixing with water, acid or incompatible materials may cause splattering and release of large amounts of heat. Will react with some metals forming flammable hydrogen gas. Carbon monoxide gas may form upon contact with reducing sugars, food and beverage products in enclosed spaces.

Incompatibilities/Materials to Avoid: Acids, Halogenated compounds, Prolonged contact with aluminum, brass, bronze, copper, lead, tin, zinc or other alkali sensitive metals or alloys

Hazardous Decomposition Products: Toxic fumes of sodium oxide

Hazardous Polymerization: Will not occur

11. TOXICOLOGICAL INFORMATION

TOXICITY DATA:

Hazardous Component	LD50 Oral	LC50 Inhalation	LD50 Dermal
Sodium hydroxide	Not listed	Not listed	1350 mg/kg (Rabbit)
Sodium chloride (NaCl)	3 g/kg (Rat)	42 g/m ³ (1 hr-Rat)	10 g/kg (Rabbit)

TOXICITY:

The severity of the tissue damage is a function of its concentration, the length of tissue contact time, and local tissue conditions. After exposure there may be a time delay before irritation and other effects occur. This material is a strong irritant and is corrosive to the skin, eyes, and mucous

membranes. This material may cause severe burns and permanent damage to any tissue with which it comes into contact. Inhalation will cause severe irritation and possible burns with pulmonary edema, which may lead to pneumonitis. Skin contact with this material may cause severe irritation and corrosion of tissue. Eye contact can cause severe irritation, corrosion with possible corneal damage and blindness. Ingestion may cause irritation, corrosion/ulceration, nausea, and vomiting. In general, chronic effects are due to long-term irritation. This material may cause dermatitis. In rare cases reports have noted long-term inhalation causes bronchial inflammatory reaction or obstructive airway dysfunction.

CARCINOGENICITY: This product is not classified as a carcinogen by NTP, IARC or OSHA.

12. ECOLOGICAL INFORMATION

AQUATIC TOXICITY: This material has exhibited moderate toxicity to aquatic organisms. Data provided are for sodium hydroxide.

Freshwater Fish Data:

LC50 brook trout: 25 ppm/24 hr

LC50 king salmon: 48 ppm

Invertebrate Toxicity Data:

EC50 daphnia magna: 100 ppm

EC50 shrimp: 33 100 ppm/48 hr

EC50 cockle: 330 1000 ppm/48 hr

BIODEGRADATION: This material is inorganic and not subject to biodegradation.

PERSISTENCE: This material is alkaline and may raise the pH of surface waters with low buffering capacity. This material is believed to exist in the disassociated state in the environment.

BIOCONCENTRATION: This material is not expected to bioconcentrate in organisms.

ADDITIONAL ECOLOGICAL INFORMATION: This material has exhibited slight toxicity to terrestrial organisms.

13. DISPOSAL CONSIDERATIONS

Reuse or reprocess, if possible. Dispose in accordance with all applicable regulations. May be subject to disposal regulations: U.S. EPA 40 CFR 261.
Hazardous Waste Number(s): D002

14. TRANSPORT INFORMATION

U.S. DOT 49 CFR 172.101:

PROPER SHIPPING NAME: Sodium Hydroxide Solution

DOT UN NUMBER: UN1824

HAZARD CLASS/ DIVISION: 8
PACKING GROUP: II
LABELING REQUIREMENTS: 8
DOT RQ (lbs): RQ 1000 lbs. (Sodium Hydroxide)

CANADIAN TRANSPORTATION OF DANGEROUS GOODS:

SHIPPING NAME: Sodium hydroxide solution
UN NUMBER: UN1824
CLASS: 8
PACKING/RISK GROUP: II

15. REGULATORY INFORMATION

U.S. REGULATIONS

OSHA REGULATORY STATUS:

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200) (US).

CERCLA SECTIONS 102a/1103 HAZARDOUS SUBSTANCES (40 CFR 302.4):

If a release is reportable under CERCLA section 103, notify the state emergency response commission and local emergency planning committee. In addition, notify the National Response Center at (800) 424-8802 or (202) 4262675.

Hazardous Component	CERCLA Reportable Quantities:
Sodium hydroxide	1000 lb (final RQ)

EPCRA EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.30): No components are listed.

EPCRA SECTIONS 311/312 HAZARD CATEGORIES (40 CFR 370.21):

Acute Health Hazard

EPCRA SECTION 313 (40 CFR 372.65): No components are listed.

OSHA PROCESS SAFETY (29 CFR 1910.119): Not regulated

NATIONAL INVENTORY STATUS

U.S. INVENTORY STATUS (TSCA): All components are listed or exempt

TSCA 12(b): This product is not subject to export notification

CANADIAN DOMESTIC SUBSTANCE LIST (DSL/NDSL): All components are listed.

STATE REGULATIONS

California Proposition 65: This product is not listed

Hazardous Component	Sodium hydroxide
---------------------	------------------

California Proposition 65 Cancer WARNING:	Not Listed
California Proposition 65 CRT List - Male reproductive toxin:	Not Listed
California Proposition 65 CRT List - Female reproductive toxin:	Not Listed
Massachusetts Right to Know Hazardous Substance List	Listed
New Jersey Right to Know Hazardous Substance List	Listed
New Jersey Special Health Hazards Substance List	Listed
Pennsylvania Right to Know Hazardous Substance List	Listed
Pennsylvania Right to Know Environmental Hazard List	Listed
Rhode Island Right to Know Hazardous Substance List	Listed

CANADIAN REGULATIONS:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Classification: E

16. OTHER INFORMATION

HMIS: (SCALE 0-4) (Rated using National Paint & Coatings Association HMIS: Rating Instructions, 2nd Edition)

Health: 3 Flammability: 0 Reactivity: 1

NFPA 704 - Hazard Identification Ratings (SCALE 0-4)

Health: 3 Flammability: 0 Reactivity: 1

Univar USA Inc Material Safety Data Sheet

For Additional Information contact MSDS Coordinator during business hours, Pacific time: (425) 889-3400

Notice

Univar USA Inc. ("Univar") expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein, and shall under no circumstances be liable for incidental or consequential damages.

Do not use ingredient information and/or ingredient percentages in this MSDS as a product specification. For product specification information refer to a product specification sheet and/or a certificate of analysis. These can be obtained from your local Univar sales office.

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, Univar makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Univar's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein.

This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process