

Safety Data Sheet



Zep, Inc.
1310 Seaboard Industrial Blvd.
Atlanta, GA 30318
1-877-I-BUY-ZEP (428-9937)
www.zep.com

Section 1. Chemical Product and Company Identification

Product name ZEPVUE R.T.U.
Product use Glass Cleaner
Product code 1010
Date of issue 11/22/13 **Supersedes** 10/25/12

Emergency Telephone Numbers

For MSDS Information:

Compliance Services 1-877-I-BUY-ZEP (428-9937)

For Medical Emergency

(877) 541-2016 Toll Free - All Calls Recorded

For Transportation Emergency

CHEMTREC: (800) 424-9300 - All Calls Recorded
In the District of Columbia (202) 483-7616

Prepared By

Compliance Services
1259 Seaboard Industrial Blvd.
Atlanta, GA 30318

Section 2. Hazards Identification

Emergency overview

*Hazard Determination System (HDS): Health, Flammability, Reactivity

WARNING!



COMBUSTIBLE LIQUID AND VAPOR. CAUSES EYE IRRITATION.
HARMFUL IF INHALED OR ABSORBED THROUGH SKIN.

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

Acute Effects

Routes of Entry

Dermal contact. Eye contact. Inhalation.

- Eyes** Causes eye irritation. Inflammation of the eye is characterized by redness, watering and itching.
- Skin** May cause skin irritation. May be harmful if absorbed through the skin. Skin inflammation is characterized by itching, scaling, or reddening.
- Inhalation** Avoid breathing vapors, spray or mists. Overexposure of this product by inhalation or absorption can produce central nervous system depression resulting in headache, nausea and/or dizziness.
- Ingestion** May be harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage.

Chronic effects

Contains material which may cause damage to the following organs: blood, kidneys, liver, spleen, lymphatic system, upper respiratory tract, skin, bone marrow, central nervous system (CNS), eye, lens or cornea. Prolonged or repeated contact may dry skin and cause irritation.

Carcinogenicity Classification No known significant effects or critical hazards.

Additional information: See toxicological information (Section 11)

Section 3. Composition/Information on Ingredients

Name	CAS number	%
Butoxyethanol; 2-butoxyethanol	111-76-2	1 - 5

Section 4. First Aid Measures

- Eye Contact** Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
- Skin Contact** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if irritation occurs.
- Inhalation** Move exposed person to fresh air. Loosen tight clothing such as a collar, tie, belt or waistband. If irritation persists, get medical attention.
- Ingestion** Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

National Fire Protection Association (U.S.A.)



Flash Point	Closed cup: 67.8°C (154°F) [Tagliabue.]
Flammable Limits	Not determined.
Flammability	Combustible
Fire hazard	Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Fire-Fighting Procedures	Use dry chemical, CO ₂ , water spray (fog) or foam. Fire-fighters should wear appropriate protective equipment.

Section 6. Accidental Release Measures

Spill Clean up	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
-----------------------	--

Section 7. Handling and Storage

Handling	Put on appropriate personal protective equipment (see Section 8). Store and use away from heat, sparks, open flame or any other ignition source. Avoid contact with eyes, skin and clothing. Avoid breathing vapors, spray or mists. Use only with adequate ventilation. Do not ingest. Observe label precautions. Wash thoroughly after handling. Empty containers retain product residue and can be hazardous. Do not reuse container.
Storage	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Keep out of the reach of children.

Section 8. Exposure Controls/Personal Protection

Ingredient	Exposure limits
Butoxyethanol; 2-butoxyethanol	OSHA PEL 1989 (United States, 3/1989). Absorbed through skin. TWA: 25 ppm 8 hours. TWA: 120 mg/m ³ 8 hours. NIOSH REL (United States, 1/2013). Absorbed through skin. TWA: 5 ppm 10 hours. TWA: 24 mg/m ³ 10 hours. ACGIH TLV (United States, 3/2012). TWA: 20 ppm 8 hours. OSHA PEL (United States, 6/2010). Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 240 mg/m ³ 8 hours.

Personal Protective Equipment (PPE)

Eyes	Safety glasses.	
Body	For prolonged or repeated handling, use gloves. Recommended: Neoprene gloves. Nitrile gloves. Rubber gloves.	
Respiratory	Use with adequate ventilation. A respirator is not needed under normal and intended conditions of product use.	

Section 9. Physical and Chemical Properties

Physical State	Liquid.	Color	Clear. Blue. [Light]
pH	10.5 to 11.5	Odor	Pleasant.
Boiling Point	100°C (212°F)	Vapor Pressure	Not available.
Specific Gravity	0.99	Vapor Density	Not available.
Solubility	Easily soluble in the following materials: cold water and hot water.	Evaporation Rate	1 (Water = 1)
		VOC (Consumer)	<3 % (w/w) <0.248 lbs/gal (<29.7 g/l)

Section 10. Stability and Reactivity

Stability and Reactivity	The product is stable.
Incompatibility	Avoid contact with strong oxidizers, excessive heat, sparks or open flame.
Hazardous Polymerization	Under normal conditions of storage and use, hazardous polymerization will not occur.
Hazardous Decomposition Products	carbon oxides (CO, CO ₂)

Section 11. Toxicological Information

Product/ingredient name	Result	Species	Dose	Exposure
Butoxyethanol; 2-butoxyethanol	LC50 Inhalation Gas.	Rat	450 ppm	4 hours
	LD50 Dermal	Rabbit	220 mg/kg	-
	LD50 Oral	Rat	250 mg/kg	-

Section 12. Ecological Information

Environmental Effects Not available.

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
Butoxyethanol; 2-butoxyethanol	Acute EC50 >1000 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 800000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 1250000 µg/l Marine water	Fish - Menidia beryllina	96 hours

Section 13. Disposal Considerations**Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

Waste Stream Classification: Non-hazardous waste by Characteristic.
Origin: RCRA waste.

Section 14. Transport Information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
DOT Classification	Not regulated.	-	-	-	
IMDG Class	Not regulated.	-	-	-	

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG* : Packing group

Section 15. Regulatory Information**U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

Product name

Butoxyethanol; 2-butoxyethanol

Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

All Components of this product are listed or exempt from listing on TSCA Inventory.

State Regulations**California Prop 65**

No products were found.

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.
Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution.
Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.