

*** MATERIAL SAFETY DATA SHEET ***

This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this material. Please read the information on these sheets, and then provide this information to those people at your company whose responsibility it is to implement the "Workplace Hazardous Materials Information System (WHMIS)". Also make this information available to any employee who requests it.

Date of preparation: 07-11-2007

3700-652A

SECTION I

PRODUCT IDENTIFICATION AND USE

Manufacturer	: W. R. MEADOWS. INC	- H M I S -
Address	: 300 Industrial Drive : Hampshire, IL 60140-0338	Health : 2 Fire : 1 Reactivity : 0 Person Protection :
Telephone #	: (847) 214-2100	
Emergency #	: 1-800-424-9300 Chemtrec	

(Hazard Rating: 0=Least,1=Slight,2=Moderate,3=High,4=Extreme,*=Chronic)

Product Class : Class D, Division 2, Subdivision B, Toxic Materials

Product Identification Number: 3700-652

Product Identifier: **SEALTIGHT REZI-WELD GEL PASTE STATE EPOXY COMPONENT A**

Product Use: Filler for sawcuts and random concrete cracks

SECTION II

HAZARDOUS INGREDIENTS

No. Hazardous Ingredient(s)*	CAS#	% By Weight	ACGIH	LD50	LC50	TLV/TWA	TLV/Ceiling	TLV/STEL	SKIN
1. Bisphenol A/Epichlorohydrin Resin	25085-38-6	60-70	N/E	N/E	N/E	N/E	N/E	N/E	N/E

* A more complete disclosure will be provided to a physician or nurse in the event of a medical emergency. None of the components of this product are recognized as carcinogenic. *: Respirable dust **: Rat

Component data is defined in accordance with Sub-paragraph 13 (a) (i) to (iv) of the Hazardous Product Act.

N/E Not established

SECTION III

PHYSICAL DATA

Physical State : Liquid **Vapor Density** : >1 (Air1)

Specific Gravity : 1.18 **Evaporation Rate** : <1 (Ether1)

Product Odor/Appearance : Amber viscous liquid/Amoniacal odor **Percent Volatile** : Not Established

Vapor Pressure : Not Established **Freezing Point** : Not Established

pH : Not Established **Boiling Point** : Greater than 196° C

Odor Threshold : Not Applicable

Coefficient of water/oil distribution: Not Applicable

SECTION IV

FIRE AND EXPLOSION DATA

Conditions of Flammability: Ignition Sources

Autoignition temperature: N/E

Means of extinction: Water fog, foam, dry chemical, or Carbon Dioxide

Sensitivity to mechanical impact: No

Flash point and method: Greater than 92° C

Sensitivity to static discharge: No

Flammability limits: LEL: N/E UEL: N/E

Hazardous combustion products: Carbon Monoxide, Carbon Dioxide and incomplete combustion products.

SECTION V

REACTIVITY DATA

Chemical stability: Stable

If no, under which conditions:

Incompatibility (materials to avoid): Strong Oxidizing Agents, Acids, Alkaline Materials, Amines, Polyamines, and Polyamides under uncontrolled conditions.

Conditions of reactivity: None

Hazardous decomposition products: None Known

SECTION VI

TOXICOLOGICAL PROPERTIES

Route(s) of entry: Inhalation, skin contact.

Effect(s) of acute exposure to product:

EYE CONTACT: This product is presumed to be irritating to the eyes. Exposure may cause corneal injury.

SKIN CONTACT: This product may cause allergic reaction in susceptible individuals. Prolonged/repeated exposure may cause skin irritation and stain the skin. Contact with the skin may result in sensitization to epoxies. Individuals who have a developed skin sensitization can develop these symptoms as a result of contact with very small amounts of liquid material or as a result of exposure to vapor. This skin sensitization may be temporary or permanent. Once an individual is diagnosed as being sensitized, no further exposure can be permitted.

(Continued)

Date of preparation: 07-11-2007

3700-652A

*** MATERIAL SAFETY DATA SHEET ***

Date of preparation:07-11-2007

3700-652A

SECTION VI (Continued)

TOXICOLOGICAL PROPERTIES

INHALATION: Exposure may produce irritation to the nose, throat, respiratory tract, and other mucous membranes.

Repeated overexposures or exposure to a single large dose may result in lung sensitization in susceptible individuals. Once an individual is diagnosed as being sensitized, no further exposure can be permitted. This lung sensitization may be temporary or permanent.

INGESTION: This product may cause mild irritation of the digestive tract.

SIGNS AND SYMPTOMS: Symptoms of eye irritation include pain, tearing, reddening, and swelling. Symptoms of skin irritation include reddening, swelling, rash, and redness. Symptoms of respiratory irritation include runny nose, sore throat, coughing, chest discomfort, shortness of breath, and reduced lung function. Symptoms of gastrointestinal irritation include sore throat, abdominal pain, nausea, vomiting, and diarrhea.

Exposure limits: See Section II.

Effect(s) of chronic exposure to product:

Carcinogenicity: No

Reproductive toxicity: No

Teratogenicity: No

Mutagenicity: No

Synergistic Properties: No

SECTION VII

PREVENTIVE MEASURES

Personal protective equipment: Wear safety glasses, goggles, or a splash shield to prevent eye contact. Contact lenses should not be worn.

Wear appropriate gloves and protective clothing to prevent contact with skin and clothing.

Engineering controls: Use ventilation as required to control vapor concentrations - at least 10 air changes per hour are recommended for good general room ventilation. If exposure exceeds the PEL/TLV, use the appropriate NIOSH approved respirator.

Leak and spill procedures: LARGE SPILLS>> Evacuate the hazard area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut off source of leak only if safe to do so. Dike and contain. If vapor cloud forms, water fog may be used to suppress; contain run-off. Remove with vacuum trucks or pump to storage/salvage vessels. Soak up residue with an absorbent such as clay, sand or other suitable material; place in non-leaking containers for proper disposal. Flush area with water to remove trace residue; dispose of flush solutions as above. SMALL SPILLS>> Take up with an absorbent material and place in non-leaking containers.

Waste disposal: Observe all Provincial, Federal, State and local regulations regarding proper disposal.

Handling procedures/equipment: Avoid direct contact with this product.

Storage requirements: Store in a cool dry area, away from ignition sources. Keep containers closed when not in use.

Special shipping information: None

SECTION VIII

FIRST AID MEASURES

EYE CONTACT: If irritation or redness develops, move victim away from exposure source and into fresh air. Flush eyes with water for fifteen (15) minutes. If symptoms persist, seek medical attention.

SKIN CONTACT: Remove contaminated shoes and clothing. Cleanse affected area(s) thoroughly by washing with mild soap and water. If irritation or redness develops and persists, seek medical attention.

INHALATION: If respiratory symptoms develop, move victim away from exposure source and into fresh air. If symptoms persist, seek medical attention. If victim is not breathing, immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

INGESTION: Do not induce vomiting. If vomiting spontaneously occurs, keep the victim's head below the hips to prevent aspiration into the lungs. Since aspiration into the lungs can cause very serious, permanent damage, the decision of whether to induce vomiting or not should be made by a physician. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Consult a physician, hospital, or poison control center and/or transport to an emergency facility immediately.

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of the product described herein.

SECTION IX

PREPARATION OF MSDS

Prepared by: David Carey

Phone number:(847) 683-4500

Preparation date: 07-11-2007

Product Identification Number: 3700-652A