

**COOPER COMPANIES****NEW CHEMICAL/SUBSTANCE USAGE APPROVAL REQUISITION**DIVISION Processing DEPARTMENT ShippingPRODUCT NAME Crown Industrial Enamel Paint DATE 12/18/24MANUFACTURED BY: Custom Aerosol Packaging SUPPLIED BY: Crown Lift Trucks**INSTRUCTIONS**

Attach a copy of (1) Product Information Sheet, (2) the supplied Material Safety Data Sheets and (3) Make sure appropriate PPE & Emergency Equipment is on site for this product before submitting for usage approval. Complete each question fully, use N/A for sections that are Not Applicable. Date and sign form.

SECTION IWHERE USED & PURPOSE: re-paint fork liftsWHERE STORED (Bldg./Room): DC Lift Maint

- PERIOD OF USAGE: ____ Days ____ Months ____ Years

Product previously used: X YES ____ NO

- DAILY MAXIMUM AMOUNT ON HAND: ____ 1 case @ 12

Type of Storage Container: can

- AMOUNT PER CONTAINER: ____

H.M.I.G: 2 Health 3 Flammability 1 Reactivity W Protective EquipmentCHEMICAL NAME (Dominant): Ethyl acetate - STATUS: ____ Solid ____ Liquid X Gas ____ Pure ____ MixtureAny special precautions or hazards? pressurized container-do not puncture or burn-use proper PPE while using**SECTION II**

WHAT WILL THIS CHEMICAL/SUBSTANCE REPLACE? List current supplier and chemical/substance trade name. _____

IS THIS A DUPLICATION? ____ YES ____ NO, IF YES, why? Be specific _____

SECTION III

DISPOSITION OF REPLACED CHEMICAL/SUBSTANCE. Complete appropriate line.

____ Return to supplier for Credit Return Authorization # _____

____ Use up prior to new substance usage. Date you will run out _____

____ Container and contents to be disposed of. List disposal service and estimated cost. _____

Requested by: Hillary SteinSignature: Hillary Stein*DO NOT MARK BELOW THIS LINE*

USAGE APPROVED _____ DATE _____ USAGE DENIED _____

COMMENTS: _____

SAFETY DIRECTOR: _____ PURCHASING: _____

SDS

GHS Safety Data Sheet

Custom Aerosol Packaging

Crown Industrial Enamel Paint

1

PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Crown Industrial Enamel Paint
Common Name: Paint
SDS Number: 0004
Revision Date: 12/31/2020
Version: 003
Supplier Details: Custom Aerosol Packaging
543 Staunton St
Piqua, Ohio 45356

063011-007 #88 Dk Gray, 063011-033 Bright Beige, 063011-008 Med Gray, 063011-009 #94 Beige, 063011-025 Alpine White
063011-027 Lt Graphite, 063011-010 #88 Blue, 063011-035 Silver Motor, 063011-029 Crystal Silver, 063011-002 Orange
063011-034 Bright Beige, 063011-037 Medium Silver, 063011-041 Ultra Marine Blue

EMERGENCY PHONE NUMBER CALL INFOTRAC: 1-800-535-5053 OR 1-352-323-3500 (OUTSIDE USA)



Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS):

Health, Acute toxicity, 4 Oral
 Health, Acute toxicity, 4 Inhalation
 Physical, Flammable Aerosols, 1
 Physical, Gases Under Pressure, Liquefied Gas

GHS Label elements, including precautionary statements

GHS Signal Word: DANGER

GHS Hazard Pictograms:

**GHS Hazard Statements:**

H302 - Harmful if swallowed
 H332 - Harmful if inhaled
 H222 - Extremely flammable aerosol
 H280 - Contains gas under pressure; may explode if heated

GHS Precautionary Statements:

P251 - Pressurized container: Do not pierce or burn, even after use.
 P102 - Keep out of reach of children.
 P211 - Do not spray on an open flame or other ignition source.
 P262 - Do not get in eyes, on skin, or on clothing.
 P271 - Use only outdoors or in a well-ventilated area.
 P285 - In case of inadequate ventilation wear respiratory protection.
 P332+313 - If skin irritation occurs: Get medical advice/attention.
 P410+412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
 P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking
 P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
 P270 - Do not eat, drink or smoke when using this product.
 P281 - Use personal protective equipment as required.
 P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Hazards not otherwise classified (HNOC) or not covered by GHS

Route of Entry: Primary Route(S) of Entry: Eye Contact, Inhalation, Skin Adsorption, Skin Contact

Target Organs: Blood, Kidney, Liver, Central nervous system

Inhalation: Harmful if inhaled. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs.

Skin Contact: Substance may cause slight skin irritation. Prolonged or repeated contact may cause skin irritation.

Eye Contact: Causes eye irritation.

Ingredients:

Cast#	%	Chemical Name
141-78-6	45-55%	Ethyl acetate
67-64-1	15-25%	Acetone
74-98-6	15-25%	Propane / Isobutane / n-Butane

FIRST AID MEASURES

Inhalation: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

Skin Contact: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

Ingestion: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention.

FIRE FIGHTING MEASURES

Flammability: EXTREMELY FLAMMABLE LIQUID AND VAPOR!

Flash Point: <30Degrees F

Flash Point Method: Setaflash Closed Cup

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flash Point is less than 30 degrees F. Extremely Flammable Liquid and Vapor! Water spray may be ineffective. Closed containers may explode when exposed to extreme heat. Vapors may form explosive mixtures with air. Vapors can travel to a source of ignition and flash back. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Perforation of the pressurized container may cause bursting of the can.

SPECIAL FIREFIGHTING PROCEDURES: Evacuate area and fight fire from a safe distance.

ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled liquid with sand or earth. DO NOT use combustible materials like sawdust. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Do not let product enter drains.

HANDLING AND STORAGE

Handling Precautions: Wash thoroughly after handling. Wash hands before eating. Use only in a well-ventilated area. Follow all SDS label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors or mist.

Storage Requirements: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Do not store above 120 degrees F. Store large quantities in buildings designed and protected for storage of NFPA Class 1 flammable liquids. Contents under pressure. Do not expose to heat or store above 120 degree F.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Precautions to be taken in use:
Use only with adequate ventilation.
Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.
Wash hands after using.
This coating may contain materials classified as nuisance particulates (listed as dust in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m³ (total dust) 3 mg/m³ (respirable fraction), OSHA PEL 15 mg/m³ (total dust) 5 mg/m³ (respirable).

Personal Protective Equipment: Ventilation:
Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

Respiratory Protection:
If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.
When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint or the abrasive.

Protective Gloves:
None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact wear chemical resistant gloves.

Eye Protection:
Wear safety spectacles with unperforated sideshields.

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Various Color Liquid	Solubility:	Not Available
Spec Grav./Density:	.74	Percent Volatile:	81.9%
Boiling Point:	241 / 386 degrees F	Freezing/Melting Pt.:	Not Available
Flammability:	Extremely Flammable	Flash Point:	< 30 degrees F
pH:	N/A	Vapor Density:	Heavier than air
Evap. Rate:	Slower than ether	VOC:	53.31%

STABILITY AND REACTIVITY

Chemical Stability:	This product is stable under normal conditions.
Conditions to Avoid:	Avoid temperatures above 120 degrees F. Avoid all possible sources of ignition.
Materials to Avoid:	Incompatible with strong oxidizing agents, strong acids and strong alkalies.
Hazardous Decomposition:	By open flame, carbon monoxide and carbon dioxide. When heated to decomposition it emits acrid smoke and irritating fumes.
Hazardous Polymerization:	Will not occur under normal conditions.

TOXICOLOGICAL INFORMATION**Chronic Health Hazards**

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Toxicology Data

Cas NO.	Ingredient Name	LC50 RAT	4HR	Not Available
74-98-6	Propane	LC50 RAT LD50 RAT	4HR	Not Available Not Available
75-28-5	Isobutane	LC50 RAT LD50 RAT	4HR	Not Available Not Available
141-78-6	Ethyl Acetate	LC50 Rats LD50 Rats	2HR	45,000 mg/m ³ 5620 mg/kg
67-64-1	Acetone	LC50 RAT LD50 RAT	4HR	Not Available 5800 mg/kg

ECOLOGICAL INFORMATION

Product is a mixture of listed components.

DISPOSAL CONSIDERATIONS

UN1950

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.) does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

US Ground (DOT)

May be classed as LTD. QTY. or ORM-D
UN 1950, AEROSOLS, 2.1 LIMITED QUANTITY, (ERG#126)

Canada (TDG)

May be classified as LTD. QTY. OR ORM-D
UN1950, AEROSOLS, CLASS 2.1 LIMITED QUANTITY (ERG#126)

IMO

May be shipped as Limited Quantity
UN1950 AEROSOLS, CLASS 2.1, LIMITED QUANTITY, EmS F-D, S-U

IATA/ICAO

UN1950, AEROSOLS, FLAMMABLE, 2.1 LIMITED QUANTITY

Component (CAS#) [%] - CODES

Ethyl acetate (141-78-6) [45-55%] CERCLA, MASS, OSHAWAC, PA, TOXICRCRA, TSCA, TXAIR, TXHWL

RQ(5000LBS), Acetone (67-64-1) [15-25%] CERCLA, HAP, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TSCA, TXAIR, TXHWL

Propane / Isobutane / n-Butane (74-98-6) [n/a%] MASS, NJHS, OSHAWAC, PA, TSCA, TXAIR

Propane / Isobutane / n-Butane (74-98-6) [15-25%] MASS, NJHS, OSHAWAC, PA, TSCA, TXAIR

Regulatory CODE Descriptions

RQ = Reportable Quantity

CERCLA = Superfund clean up substance

MASS = MA Massachusetts Hazardous Substances List

OSHAWAC = OSHA Workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

TOXICRCRA = RCRA Toxic Hazardous Wastes (U-List)

TSCA = Toxic Substances Control Act

TXAIR = TX Air Contaminants with Health Effects Screening Level

TXHWL = TX Hazardous Waste List

HAP = Hazardous Air Pollutants

NJHS = NJ Right-to-Know Hazardous Substances


SARA313 = SARA 313 Title III Toxic Chemicals

NFPA: Health = 2, Fire = 3, Reactivity = 1, Specific Hazard = POLY

HMIS III: Health = 2(Chronic), Fire = 3, Physical Hazard = 1

HMIS W - Dust and Vapor Respirator

PPE:



HMIS	
HEALTH	<input checked="" type="checkbox"/> 2
FLAMMABILITY	3
PHYSICAL HAZARD	1
PERSONAL PROTECTION	W

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR. The responsibility to provide a safe workplace remains with the user. The user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment. The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by the use of this material. It is the responsibility of the user to comply with all applicable laws and regulations applicable to this material.

Revision Date: 12/31/2020