



Material Safety Data Sheet

Section 1. Chemical Product and Company Identification

Product name DYNA 143
Product use Parts Cleaner
Product code 0366
Date of issue 06/10/16 **Supersedes** 10/25/13

Emergency Telephone Numbers

For MSDS Information:

Technical Services Group
Telephone (780) 453-8100
(Business Hours 8:00am - 5:00pm)

For Medical or Transportation Emergency

CANUTEC (24 Hours)
(613) 996-6666 - Call Collect

Prepared By

Technical Services Group
11627 178th Street
Edmonton, Alberta T5S 1N6

Section 2. Hazards Identification

Emergency overview

CAUTION !

COMBUSTIBLE LIQUID AND VAPOR.

Combustible liquid. Keep away from heat, sparks and flame. Avoid breathing vapor or mist. Avoid contact with skin and clothing. Use only with adequate ventilation.

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

Acute Effects

Routes of Entry

Eye contact, Skin, Inhalation.

Eyes May cause eye irritation. Inflammation of the eye is characterized by redness, watering and itching.

Skin May cause skin irritation. Skin inflammation is characterized by itching, scaling, or reddening.

Inhalation Harmful by inhalation. Over-exposure by inhalation may cause respiratory irritation. Can cause central nervous system (CNS) depression. Pre-existing respiratory disorders may be aggravated by over-exposure to this product.

Ingestion Aspiration hazard if swallowed. Can enter lungs and cause damage.

Chronic effects

Prolonged skin contact may cause dermatitis with drying and cracking of skin. Skin which is repeatedly defatted by contact with this product may be more susceptible to irritation, infection or dermatitis.

Additional Information: See Toxicological Information (Section 11)

Section 3. Composition/Information on Ingredients

Name of Hazardous Ingredients

LIGHT ALIPHATIC NAPHTHA; solvent naphtha (petroleum), medium aliphatics

CAS number

64742-88-7

% by Weight

60 - 100

Section 4. First Aid Measures

Eye Contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Skin Contact Flush affected skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Inhalation Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention if adverse health effects persist or are severe.

Ingestion	If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Never give anything by mouth to an unconscious person. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get immediate medical attention.
------------------	--

Section 5. Fire Fighting Measures

Flash Point	Closed cup: 62°C (143.6°F) [Pensky-Martens.]
Flammable Limits	Lower: 1% Upper: 7%
Flammability	Combustible liquid.
Auto-ignition Temperature	
Fire-Fighting Procedures	Use dry chemical, CO ₂ , water spray (fog) or foam. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Fire hazard	Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.
Products of Combustion	May emit toxic fumes under fire conditions. carbon oxides (CO, CO ₂)
Explosion hazard	Not available.

Section 6. Accidental Release Measures

Spill Clean up	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.
-----------------------	--

Section 7. Handling and Storage

Handling	Put on appropriate personal protective equipment (see Section 8). Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. Do not reuse container. Wash thoroughly after handling.
Storage	Do not store above the following temperature: 49°C (120°F). Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Do not store in unlabeled containers. Keep out of the reach of children.

Section 8. Exposure Controls/Personal Protection

<u>Product name</u>	<u>Exposure limits</u>
No exposure limit value known.	

Personal Protective Equipment (PPE)



Eyes	Recommended: Splash goggles.
Hands and	Recommended: Neoprene gloves. Nitrile gloves. Rubber gloves.
Body	
Respiratory	Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Wear appropriate respirator when ventilation is inadequate. Approved/certified respirator with organic vapor cartridge.

Section 9. Physical and Chemical Properties

Physical State	Liquid.	Color	Colorless.
pH	Not available.	Odor	Mild.
Boiling Point	187°C (368.6°F)	Vapor Pressure	< 1.0 @ 20°C
Specific Gravity	0.79	Vapor Density	5.3 [Air = 1]
Solubility	Insoluble in the following materials: cold water.	Evaporation Rate	0.14 (Butyl acetate. = 1)
Freezing Point		VOC (Consumer)	100% (789 g/L; 6.58 lbs/gal)

Section 10. Stability and Reactivity

Stability and Reactivity	The product is stable.
Incompatibility	Reactive or incompatible with the following materials: oxidizing materials. Keep away from heat, sparks and flame.
Hazardous Polymerization	Will not occur.
Hazardous Decomposition Products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological Information

Carcinogenicity No known significant effects or critical hazards. Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

Acute Toxicity

Not available.

Section 12. Ecological Information

Environmental Effects No known significant effects or critical hazards.

Aquatic Ecotoxicity

Not available.

Section 13. Disposal Considerations**Waste Information**

Waste must be disposed of in accordance with applicable regulations. Consult your local or regional authorities for additional information.

Waste Stream**Section 14. Transport Information**

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
TDG Classification	Not regulated.	-	-	-		-
IMDG Class	Not available.	Not available.	Not available.	-		-

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment. **Limited Quantity:** Small quantities of controlled goods are not regulated as Dangerous Goods according to TDG regulations.

PG* : Packing group

Section 15. Regulatory Information**Canada**

WHMIS (Canada) Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.