



MATERIAL SAFETY DATA SHEET

MSDS NUMBER ▶ 80,070-8

PAGE 1

97367 (4-85)

24 HOUR EMERGENCY ASSISTANCE			GENERAL MSDS ASSISTANCE		
SHELL: 713-473-9461 CHEMTREC: 800-424-9300			SHELL: 713-241-4819		
ACUTE HEALTH + 3	FIRE 1	REACTIVITY 0	HAZARD RATING ▶ LEAST - 0 SLIGHT - 1 MODERATE - 2 HIGH - 3 EXTREME - 4		
*For acute and chronic health effects refer to the discussion in Section III					



SECTION I	NAME
PRODUCT ▶	SHELLZONE(R) ANTIFREEZE
CHEMICAL NAME ▶	ETHYLENE GLYCOL
CHEMICAL FAMILY ▶	GLYCOL
SHELL CODE ▶	32350 94010 94012

SECTION II-A		PRODUCT/INGREDIENT	
NO.	COMPOSITION	CAS NUMBER	PERCENT
P	SHELLZONE ANTIFREEZE	MIXTURE	100
1	ETHYLENE GLYCOL	107-21-1	84-94
2	DIETHYLENE GLYCOL	111-46-6	0-10
3	WATER	7732-18-5	2-4
4	INORGANIC/ORGANIC SALTS		2-4

SECTION II-B		ACUTE TOXICITY DATA	
NO.	ACUTE ORAL LD50	ACUTE DERMAL LD50	ACUTE INHALATION LC50
1	4.0 G/KG - RAT	19.5 G/KG - RABBIT	NONE
1	5.0 G/KG - RABBIT	11.9 G/KG - RABBIT	NONE
2	14.8 G/KG - RAT		

BASED UPON DATA AVAILABLE TO SHELL, COMPONENTS 3 AND 4 IN THIS PRODUCT ARE NOT HAZARDOUS UNDER OSHA HAZARD COMMUNICATION (29 CFR 1910.1200).

SECTION III HEALTH INFORMATION

THE HEALTH EFFECTS NOTED BELOW ARE CONSISTENT WITH REQUIREMENTS UNDER THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200).

EYE CONTACT

BASED ON PRESENCE OF COMPONENT 1, PRODUCT IS MODERATELY TO SEVERELY IRRITATING TO THE EYES. VAPORS CAN ALSO CAUSE SEVERE EYE IRRITATION.

SKIN CONTACT

BASED ON PRESENCE OF COMPONENTS 1 AND 2, PRODUCT IS MILDLY IRRITATING TO THE SKIN AND SLIGHTLY TOXIC ON PROLONGED OR REPEATED CONTACT.

INHALATION

VAPORS ARE MILDLY TO MARKEDLY IRRITATING TO THE LUNGS DEPENDING ON THE EXPOSURE LEVEL.

INGESTION

PRODUCT MAY BE HARMFUL OR FATAL IF SWALLOWED; MAY PRODUCE CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION AND KIDNEY DAMAGE WHICH MAY BE FATAL. INGESTION OF COMPONENT 2 MAY ALSO PRODUCE LIVER DAMAGE.

SIGNS AND SYMPTOMS

IRRITATION AS NOTED ABOVE. EARLY TO MODERATE CNS DEPRESSION MAY BE EVIDENCED BY GIDDINESS, HEADACHE, DIZZINESS AND NAUSEA; IN EXTREME CASES, UNCONSCIOUSNESS AND DEATH MAY OCCUR. KIDNEY DAMAGE MAY BE EVIDENCED BY CHANGES IN URINE OUTPUT, URINE APPEARANCE OR EDEMA (SWELLING FROM FLUID RETENTION). LIVER DAMAGE MAY BE EVIDENCED BY LOSS OF APPETITE, JAUNDICE (YELLOWISH SKIN COLOR) AND SOMETIMES PAIN IN THE UPPER ABDOMEN ON THE RIGHT SIDE.

AGGRAVATED MEDICAL CONDITIONS

PREEXISTING SKIN, EYE, AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. IMPAIRED KIDNEY AND LIVER FUNCTIONS FROM PREEXISTING DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

OTHER HEALTH EFFECTS

INTENTIONAL ABUSE, MISUSE OR OTHER MASSIVE EXPOSURE MAY CAUSE MULTIPLE ORGAN DAMAGE AND/OR DEATH.

SEE SECTION VI FOR ADDITIONAL INFORMATION.

SECTION IV OCCUPATIONAL EXPOSURE LIMITS

NO.	PEL/TWA	OSHA	PEL/CEILING	TLV/TWA	ACGIH	TLV/STEL	OTHER
P	NONE ESTABLISHED						
1		50 PPM		50 PPM-CEILING			
1				10 MG/M3	20 MG/M3		

CEILING VALUE IS FOR EG VAPORS, OTHERS ARE FOR EG PARTICULATES.

SECTION V EMERGENCY AND FIRST AID PROCEDURES

CONTACT

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.

SKIN CONTACT

FLUSH SKIN WITH WATER. IF IRRITATION OCCURS, GET MEDICAL ATTENTION.

INHALATION

REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GET MEDICAL ATTENTION.

INGESTION

DO NOT GIVE LIQUIDS IF VICTIM IS UNCONSCIOUS OR VERY DROWSY. OTHERWISE, GIVE NO MORE THAN 2 GLASSES OF WATER AND INDUCE VOMITING BY GIVING 30CC (2 TABLESPOONS) SYRUP OF IPECAC.* IF IPECAC IS UNAVAILABLE, GIVE 2 GLASSES OF WATER AND INDUCE VOMITING BY TOUCHING FINGER TO BACK OF VICTIM'S THROAT. KEEP VICTIM'S HEAD BELOW HIPS WHILE VOMITING. GET MEDICAL ATTENTION.

NOTE TO PHYSICIAN

*IF VICTIM IS A CHILD, GIVE NO MORE THAN 1 GLASS OF WATER AND 15CC (1 TABLESPOON) SYRUP OF IPECAC. IF SYMPTOMS SUCH AS LOSS OF GAG REFLEX, CONVULSIONS OR UNCONSCIOUSNESS OCCUR BEFORE EMESIS, GASTRIC LAVAGE SHOULD BE CONSIDERED FOLLOWING INTUBATION WITH A CUFFED ENDOTRACHEAL TUBE.

SECTION VI SUPPLEMENTAL HEALTH INFORMATION

RARE CASE REPORTS OF ETHYLENE GLYCOL SENSITIZATION (ALLERGY) HAVE BEEN PUBLISHED BUT ALLERGY TO ETHYLENE GLYCOL IS NOT A COMMON PHENOMENON.

IN ONE STUDY, WHEN ETHYLENE GLYCOL WAS ADMINISTERED IN THE DIET AT DAILY DOSES UP TO 1.0 G/KG TO PREGNANT RATS, NO MATERNAL TOXICITY, NO EMBRYOTOXICITY NOR TERATOGENICITY WERE OBSERVED. IN A MORE RECENT STUDY, WHEN ETHYLENE GLYCOL WAS ADMINISTERED BY GAVAGE AT DAILY DOSES OF 1.25 G/KG AND ABOVE TO PREGNANT RATS, OR AT 750 MG/KG AND ABOVE TO PREGNANT MICE, THERE WAS AN INCREASE IN THE NUMBER OF MALFORMED FETUSES AT ALL DOSE LEVELS. EXCEPT AT THE LOWEST DOSE LEVEL IN MICE, THERE WAS ALSO EVIDENCE OF MATERNAL TOXICITY AT ALL DOSE LEVELS.

SECTION VII **PHYSICAL DATA**

BOILING POINT: 330-340 (DEG F) SPECIFIC GRAVITY: 1.1373 (H2O=1) VAPOR PRESSURE: N/AV (MM HG)

MELTING POINT: N/AV (DEG F) SOLUBILITY: COMPLETE (IN WATER) VAPOR DENSITY: >1 (AIR=1)

EVAPORATION RATE (N-BUTYL ACETATE = 1): <0.01 POUR POINT = -40 DEG. F

APPEARANCE AND ODOR:
BLUE GREEN, SLIGHTLY VISCOUS LIQUID. MILD ODOR.

SECTION VIII **FIRE AND EXPLOSION HAZARDS**

FLASH POINT AND METHOD: 246 DEG. F SETAFLASH FLAMMABLE LIMITS /% VOLUME IN AIR
LOWER: N/AP UPPER: N/AP

EXTINGUISHING MEDIA
USE WATER FOG, "ALCOHOL" FOAM, DRY CHEMICAL OR CO2.

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS
MATERIAL WILL NOT BURN UNLESS PREHEATED. DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL BUNKER GEAR (HELMET WITH FACE SHIELD, BUNKER COATS, GLOVES AND RUBBER BOOTS), INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER.

SECTION IX **REACTIVITY**

STABILITY: STABLE HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS AND MATERIALS TO AVOID:
KEEP AWAY FROM STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS
CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

SECTION X **EMPLOYEE PROTECTION**

RESPIRATORY PROTECTION
IF EXPOSURE MAY OR DOES EXCEED OCCUPATIONAL EXPOSURE LIMITS (SEC. IV) USE A NIOSH-APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE. IN ACCORD WITH 29 CFR 1910.134 USE EITHER AN ATMOSPHERE-SUPPLYING RESPIRATOR OR AN AIR-PURIFYING RESPIRATOR FOR ORGANIC VAPORS.

PROTECTIVE CLOTHING
AVOID CONTACT WITH EYES. WEAR CHEMICAL GOGGLES IF THERE IS LIKELIHOOD OF CONTACT WITH EYES. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. WEAR CHEMICAL RESISTANT GLOVES AND OTHER CLOTHING AS REQUIRED TO MINIMIZE CONTACT. TEST DATA FROM PUBLISHED LITERATURE AND/OR GLOVE AND CLOTHING MANUFACTURERS INDICATE THE BEST PROTECTION IS PROVIDED BY NITRILE, NEOPRENE, PVC OR NATURAL RUBBER GLOVES.

ADDITIONAL PROTECTIVE MEASURES

VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS. EYE WASH FOUNTAINS AND SAFETY SHOWERS
SHOULD BE AVAILABLE FOR EMERGENCY USE.

SECTION XI ENVIRONMENTAL PROTECTION

SPILL OR LEAK PROCEDURES

MAY BURN ALTHOUGH NOT READILY IGNITABLE. USE CAUTIOUS JUDGMENT WHEN CLEANING UP LARGE SPILLS. ***
LARGE SPILLS *** WEAR RESPIRATOR AND PROTECTIVE CLOTHING AS APPROPRIATE. SHUT OFF SOURCE OF LEAK
IF SAFE TO DO SO. DIKE AND CONTAIN. REMOVE WITH VACUUM TRUCKS OR PUMP TO STORAGE/SALVAGE VESSELS.
SOAK UP RESIDUE WITH AN ABSORBENT SUCH AS CLAY, SAND OR OTHER SUITABLE MATERIAL; DISPOSE OF
PROPERLY. FLUSH AREA WITH WATER TO REMOVE TRACE RESIDUE. *** SMALL SPILLS *** TAKE UP WITH AN
ABSORBENT MATERIAL AND DISPOSE OF PROPERLY.

SECTION XII SPECIAL PRECAUTIONS

STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM FLAMES AND HIGH TEMPERATURES.
WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. LAUNDRY
CONTAMINATED CLOTHING BEFORE REUSE.

SECTION XIII TRANSPORTATION REQUIREMENTS

DEPARTMENT OF TRANSPORTATION CLASSIFICATION:
NOT HAZARDOUS BY D.O.T. REGULATIONS

SECTION XIV OTHER REGULATORY CONTROLS

THE COMPONENTS OF THIS PRODUCT ARE LISTED ON THE EPA/TSCA INVENTORY OF CHEMICAL SUBSTANCES.
IN ACCORDANCE WITH SARA TITLE III, SECTION 313, THE EDS SHOULD ALWAYS BE COPIED AND SENT WITH THE
MSDS.

SECTION XV SPECIAL NOTES

THE OCCUPATIONAL EXPOSURE LIMITS (SECTION IV) AND/OR THE RESPIRATORY PROTECTION PRECAUTIONS
(SECTION X) HAVE BEEN REVISED.

THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT.
HOWEVER, SHELL MAKES NO WARRANTY, EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE
RESULTS TO BE OBTAINED FROM THE USE THEREOF. SHELL ASSUMES NO RESPONSIBILITY FOR INJURY FROM THE
USE OF THE PRODUCT DESCRIBED HEREIN.

DATE PREPARED: JUNE 28, 1989

J. C. WILLETT

BE SAFE

READ OUR PRODUCT
SAFETY INFORMATION ...AND PASS IT ON
(PRODUCT LIABILITY LAW
REQUIRES IT)

SHELL OIL COMPANY
PRODUCT SAFETY AND COMPLIANCE
P. O. BOX 4320
HOUSTON, TX 77210