

39, 40, 41

071210

ZINC NACIONAL, S.A.
MATERIAL SAFETY DATA SHEET

PRODUCT IDENTIFICATION

SECTION 1

1) PRODUCT NAME:	MAXIMO 720 / MAXIMO 721 - ZINC OXIDE		
2) EMERGENCY PHONE NO.:	011 (528) 343-85-80 & (528) 342-87-13		
3) CHEMICAL NAME:	ZINC OXIDE.	HEALTH:	FLAMMABILITY:
4) CHEMICAL FAMILY:	ZINC COMPOUNDS	2	0
5) CHEMICAL FORMULA:	ZnO	DEGREE OF HAZARD:	0 - MINIMUM HAZARD
6) MANUFACTURER'S NAME:	ZINC NACIONAL, S.A.	1	1 - SLIGHT HAZARD
7) MANUFACTURER'S ADDRESS:	SERAFIN PEÑA #938 SUR MONTERREY, N.L. MEXICO, 64000	2	2 - MODERATE HAZARD
		3	3 - SERIOUS HAZARD
		4	4 - SEVERE HAZARD
		8) DATE PREPARED	
		JANUARY, 2002	

CHEMICAL COMPOSITION

SECTION 2

INGREDIENT	CHEMICAL NAME	CAS NO.	PERCENT
ZINC OXIDE	ZINC OXIDE	1314-13-2	68.0
LEAD		7439-92-1	0.05
CADMIUM		7440-43-9	0.01

LEAD AND CADMIUM ARE INHERENT IN THE MANUFACTURE OF ZINC OXIDE AND ARE NOT PHYSICALLY ADDED IN ITS MANUFACTURE.

HAZARDOUS INGREDIENTS AND IDENTITY INFORMATION

SECTION 3

MATERIAL	FORM	EXPOSURE CRITERIAS			
		OSHA		NIOSH	
		PEL	REL	CEL	ACGIH
ZINC OXIDE	TOTAL DUST RESPIRABLE FRACTION	mg/m ³	mg/m ³	mg/m ³	mg/m ³
		15	5	—	10
		5	—	—	—

PHYSICAL DATA

SECTION 4

1) APPEARANCE / ODOR:	YELLOW-WHITE, ODORLESS POWDER	8) VAPOR PRESSURE (mm/Hg):	N/A
2) PHYSICAL STATE:	SOLID	9) VAPOR DENSITY (AIR=1):	N/A
3) BOILING POINT:	N/A	10) EVAPORATION RATE:	N/A
4) MELTING POINT:	> 1,800 °C	11) PERCENT VOLATILES:	N/A
5) SPECIFIC GRAVITY (WATER=1):	5.607 (20°C / 4°C)		
6) pH (RECOMMENDED DISSOLUTIONS):	8.70		
7) SOLUBILITY IN WATER:	GR./100 GR. WATER AT 25°C 3.5 X 10 ⁻¹ (77°F)		

FIRE AND EXPLOSION HAZARD DATA

SECTION 5

FLASH POINT:	NOT COMBUSTIBLE
EXTINQUISHING MEDIA:	FOAM, WATER, DRY CHEMICAL OR CARBON DIOXIDE.
SPECIAL FIRE FIGHTING PROCEDURES:	POISONOUS GASES ARE PRODUCED IN FIRE. WEAR FULL PROTECTIVE CLOTHING, SELF-CONTAINED BREATHING APPARATUS OPERATED IN PRESSURE-Demand MODE.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	IN POWDER FORM, ZINC OXIDE IS A MODERATE FIRE AND EXPLOSION HAZARD. WILL ALSO BURN VIGOROUSLY ON CONTACT WITH FLAME OR BY CHEMICAL REACTION.

PRODUCT NAME: MAXIMO 720 | MAXIMO 721 - ZINC OXIDE

REACTIVITY DATA

SECTION 6

1) THERMAL STABILITY: STABLE
2) CONDITIONS TO AVOID: ZINC OXIDE IS STABLE IN CLOSED CONTAINERS AT ROOM TEMPERATURE UNDER ROUTINE CONDITIONS OF STORAGE AND HANDLING. IT CAN ABSORB CARBON DIOXIDE FROM AIR TO FORM ZINC CARBONATE.
3) HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: N/A
4) HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
5) INCOMPATIBILITY (MATERIALS TO AVOID): MINERAL ACIDS, SULFUR, CHLORINATED HYDROCARBONS OR MAGNESIUM (WHEN HEATED).
6) CORROSIVE ACTION ON MATERIALS: N/A

IMPORTANT: ZINC OXIDE AND MAGNESIUM REACT EXPLOSIVELY WHEN HEATED TOGETHER.

HEALTH HAZARD DATA

SECTION 7

1) EYE AND SKIN CONTACT: WASH SKIN AREA WITH SOAP (DO NOT USE DETERGENT) AND WATER. MAY CAUSE IRRITATION.
2) INHALATION: BED REST AND ASPIRIN (SYMPTOMS USUALLY DISAPPEAR WITHIN 24 HOURS). MAY IRRITATE THE RESPIRATORY TRACT. MAY INCREASE THE INCIDENCE OF UPPER RESPIRATORY INFECTIONS.
3) INGESTION: ZINC OXIDE IS POORLY ABSORBED THROUGH THE DIGESTIVE TRACT. INGESTION MAY CAUSE GASTRITIS DUE TO THE FORMATION OF ZINC CHLORIDE IN REACTION TO STOMACH ACIDS.
4) EMERGENCY AND FIRST AID PROCEDURES: FOR INHALATION REMOVE TO FRESH AIR AND SEEK MEDICAL ATTENTION FOR ANY BREATHING DIFFICULTY. SKIN CONTACT: WASH WITH SOAP AND WATER. EYE CONTACT: FLUSH EYES IMMEDIATELY WITH WATER FOR AT LEAST 15 MIN. IF INGESTED, INDUCE VOMITING IMMEDIATELY BY GIVING TWO GLASSES OF WATER AND STICKING FINGER DOWN THROAT; NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. IN ALL CASES CONSULT PHYSICIAN FOR MEDICAL ATTENTION

PRECAUTIONS FOR SAFE HANDLING AND USE

SECTION 8

1) MATERIAL RELEASE OR SPILL: VENTILATE AREA. CLEAN UP PERSONNEL REQUIRE RESPIRATORY PROTECTION. COLLECT POWDER MATERIALS AND DEPOSIT IN SEALED DRUMS. VACUM OR SWEEP REMAINING MATERIAL (DON'T DRY SWEEP). DISPOSE IN A CLOSED CONTAINER OR HEAVY BAG. MATERIAL MAY BE RECYCLED OR DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL ENVIRONMENTAL REGULATIONS. THIS MATERIAL MAY BE REGULATED UNDER CERCLA, TSCA, SARA AND/OR RCRA REGULATIONS.
2) WASTE DISPOSAL METHOD: PROTECT BAGS FROM PHYSICAL DAMAGE. STORE IN DRY AREAS. AVOID CONTACT IN STORAGE WITH INCOMPATIBLE MATERIALS.
3) HANDLING AND STORING: LIMIT EXPOSURE OF PERSONNEL, IF POSSIBLE. PRECLUDE FROM EXPOSURE THOSE INDIVIDUALS WITH PULMONARY AND CARDIAC DISEASES. USE ADEQUATE VENTILATION.
4) PRECAUTIONARY LABELING:

CONTROL MEASURES AND PERSONAL PROTECTIVE EQUIPMENT

SECTION 9

1) VENTILATION: GENERAL EXHAUST.
2) RESPIRATORY PROTECTION: USE NIOSH APPROVED PARTICULATE RESPIRATOR IF DUST GENERATION OCCURS.
3) PROTECTIVE GLOVES: NATURAL RUBBER GLOVES.
4) EYE PROTECTION: SAFETY GOGGLES ARE RECOMMENDED.
5) WORKING UNIFORM: NORMAL.

ALWAYS WASH HANDS THOROUGHLY AFTER USING CHEMICAL; NEVER BRING FOOD, DRINK OR SMOKING MATERIALS INTO VICINITY OF CHEMICALS.

DISCLAIMER: AS THE CONDITIONS OR METHODS OF USE ARE BEYOND OUR CONTROL, WE DO NOT ASSUME ANY RESPONSIBILITY AND EXPRESSLY DISCLAIM ANY LIABILITY FOR ANY USE OF THE MATERIAL. INFORMATION CONTAINED HEREIN IS BELIEVED TO BE TRUE AND ACCURATE BUT ALL STATEMENTS OR SUGGESTIONS ARE MADE WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, REGARDING ACCURACY OF THE INFORMATION, THE HAZARDS CONNECTED WITH THE USE OF THE MATERIAL OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.