



SECTION I- Chemical Product and Company Identification

Product Identifier:

CAT OIL

Manufacturer:

Industrial Lubricants, LLC dba CAToil
5745 E. Duane Ln.
Cave Creek, AZ 85331

Product use:

Used as lubricant

Emergency Phone Number:

Chemtrec 1-800-424-9300

24 hr Emergency No.

480-515-1111

Business Hour Number

SECTION II Composition/ Information on Ingredients

Hazardous Ingredients	Concentration %	C.A.S. #	LD₅₀ (Species/Route)	LC₅₀ (Species/Route)
Lubricating oils, petroleum, hydrotreated spent	20 – 85	64742-58-1	> 2000mg/kg (rabbit/skin)	Not available
Residual oils (petroleum), solvent-dewaxed	0 – 65	64742-62-7	>2000mg/kg (rabbit/skin)	Not available
Residual oils (petroleum), hydrotreated	0 – 65	64742-57-0	Not available	Not available
Lubricating oils, petroleum, C>25, hydrotreated bright-stock based	0 – 65	72623-83-7	>3000mg/kg (rabbit/skin)	Not available
Additive containing mineral oil	0 – 7	Proprietary	>2000mg/kg (rabbit/skin)	Not available
Mineral Oil	0 – 1.5	Proprietary	Not available	Not available
Zinc dialkyldithiophosphates	0 – 1	Proprietary	Not available	Not available

SECTION III Hazards Identification

Emergency Overview

No hazards under normal conditions of use.

Potential Health Effects

Route of entry

Ingestion

Skin and eye contact are the primary routes of exposure to this product. No significant hazard. Minimal toxicity. Ingestion of large amounts may cause intestinal blockage. If drawn into lungs from swallowing or vomiting, may cause bronchopneumonia or pulmonary edema.

Inhalation

No inhalation dangers at room temperature as there are no vapours. If product is misted at elevated temperature, high concentration of vapour and/or mist may cause irritation, experienced as nasal discomfort and discharge.



Skin Contact	Frequent or prolonged contact may irritate the skin and cause a skin rash.
Eye Contact	Slight irritation to the eyes but will not cause injury to the eye tissue.
Effects of Chronic Exposure	Repeated exposure over prolonged periods of time may cause irritation to the skin, respiratory system and eyes. Follow good industrial hygiene practices to avoid exposure.
Effects of Acute Exposure	Breathing mist caused by high temperature or swallowing large quantities may be irritating to skin, respiratory system, mucous membranes and eyes.

SECTION IV First Aid Measures

Ingestion	Do not induce vomiting. Call physician immediately.
Skin Contact	Wash well with soap and water. Launder clothes prior to re-use.
Inhalation	If excessive fumes, remove victim to fresh air. If no relief is obtained, consult physician.
Eye Contact	Flush with clean tepid water for 15 minutes keeping eyelids open. If irritation persists, consult physician.
Notes to Physician	Not available.

SECTION V Fire-Fighting Measures

Flammability	Non flammable at ambient temperature. Liquid may burn at temperatures above flash point if exposed to an open flame.
Means of Extinction	Carbon dioxide foam, dry chemicals, water spray or water fog. Water or foam may cause frothing. Keep containers cool with water spray. When fighting fire, treat as petroleum product, wear full protective clothing, including NIOSH approved self-contained breathing apparatus. Avoid spreading with water flooding.
Flash Point (ASTM D92)	180°C (356°F) COC
Upper Flammability Limits	Not Determined.
Lower Flammability Limits	Not Determined.
Auto Ignition Temperature	Not available
Hazardous Combustion Products	May produce aldehydes, hydrogen sulfide, alkyl mercaptans, sulfides, nitrogen oxides, phosphorus oxides, sulfur oxides, carbon monoxide and unidentified organic compounds.
Fire and Explosion Hazards	None.
Sensitivity to Static Discharge	None at normal temperatures below flash point. Do not cut, weld, or pressurize empty container. Container may explode in heat of fire.

SECTION VI Accidental Release Measures

Personal Protection	Wear suitable protective equipment. Eliminate sources and or potential sources of ignition.
Environmental Precautions	Product is partially soluble in water. Do not flush to sewers, streams or other bodies of water. For disposal, see Section XIII.
Methods for cleaning up	Absorb on inert material such as sand, earth, vermiculite. Sweep up and collect in a suitable container for disposal. Observe government regulations.
Large spills	Stop leak if without risk. Dike to contain spill. Pump excess material into suitable container (metal drums, metal tanks, or such).

SECTION VII Handling and Storage

Handling	Avoid excess heat, formation of oil mist, breathing vapours and mist from hot oil, and prolonged or repeated contact with skin.
Storage	Store in a cool well ventilated area. Keep away from heat spark and open flame.



SECTION VIII Exposure Controls / Personal Protection

Exposure Limits

Component	Value	Type	Remark
Mineral Oil Mist	5 mg/m ³ 10 mg/m ³	TWA (mist) ACGIH STEL(mist) ACGIH	If used in a way that generates a mist, observe the limits for mineral oil mist

Engineering Controls	For normal application, special ventilation is not necessary. If user's operation generates mist, use ventilation to keep exposure to airborne contaminants below exposure limits. Make up air should always be supplied to balance air removed by exhaust ventilation.
Respiratory Protection	Use approved respirator with dual organic vapor / mist and particulate cartridge if vapor concentration exceeds permissible exposure limit. Use Self-Contained Breathing Apparatus in high vapour concentrations.
Eye Protection	Use chemical splash goggles if risk of splashing present.
Skin Protection	Use rubber or plastic apron.
Hand Protection	Use oil resistant gloves.

SECTION IX Physical and Chemical Properties

Physical State:	Liquid
Specific Gravity:	0.88 at 20°C (68°F)
Odour:	Mild petroleum odour
Odour Threshold:	Not established
Vapor Density:	Not available
Vapour Pressure:	Not available
Partitioning Coefficient:	Not available
Evaporation Rate:	Not available
Boiling Point:	>230°C (>446°F)
Pour Point:	-18°C (-0.8°F)
Solubility in Water:	Insoluble
pH:	Not available
Vapor Pressure:	less than 0.1mmHg at 20°C (68°F)

SECTION X Stability and Reactivity

Chemical Stability:	Stable
Incompatibility:	Avoid contact with oxidizing agents, reducing agents, acids and/or ignition source.
Reactivity:	No reactivity
Polymerization:	Will not occur

SECTION XI Toxicological Information

Irritancy / Route of Entry:	
Skin Contact	Frequent or prolonged contact may irritate the skin and cause a skin rash.
Skin Absorption	No evidence of adverse effects from available information. Prolonged contact may cause mild irritation.
Eye Contact	Slight irritation to eyes, but will not injure eye tissue.
Inhalation	No inhalation dangers at room temperature as there are no vapours. If the product is misted, high concentrations of vapours and/or mist may cause irritation, experienced as nasal discomfort and discharge.
Ingestion	No significant hazard. Minimal toxicity. Ingestion of large amounts may cause intestinal obstruction. If drawn into lungs from swallowing or vomiting, may cause bronchopneumonia or pulmonary edema.
Sensitization:	Repeated or prolonged contact may cause sensitization in some individuals.



Carcinogenicity:	This product contains material that has not been listed as a carcinogen or potential carcinogen by either the National Toxicology Program, International Agency for Research on Cancer, or the Occupational Safety and Health Administration.
Reproductive Toxicity:	No information is available and no adverse effects are anticipated.
Teratogenicity:	No information is available and no adverse effects are anticipated.
Mutagenicity:	No information is available and no adverse effects are anticipated.

SECTION XII Ecological information

Environmental Fate:	Base fluid has the potential for degradation by bacteria over an extended period of time. Similar product base oil are 57-88% biodegradable in 28 days.
Environmental Effects:	Based on toxicity of similar products, base oils have low toxicity toward aquatic organisms. LC50 (Rainbow Trout): >400,000 ppm in 96 hours (0% mortality). LC50 (Mysidopsis bahai): > 500,000 ppm in 96 hours. Passed the EPS !/RM/24 Microtox test using photoluminescent bacteria

SECTION XIII Disposal Consideration

RCRA 40 CFR 261 Classification

Not listed

US EPA Waste Number / Classification

Not available

Waste Disposal

Dispose of waste material in compliance with all federal, state, provincial and local regulations. Incinerate in a furnace or bury in an approved landfill where permitted under appropriate federal, provincial and local regulations.

SECTION XIV Transport Information

Department of Transport:	Not regulated under DOT
TDG – Canada	Not regulated under TDG.
DOT/TDG Proper Shipping Name:	None
DOT/TDG Hazard Class:	None
UN Number:	None
Packing Group:	None
DOT/TDG Labels:	Primary: None required Subsidiary: None required
DOT/TDG Placards:	None required

SECTION XV Regulatory Information

CPR Compliance: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations.

OSHA Hazard Communication Standards 29CFR 1910.1200: This product is not known to contain any of the carcinogens required to be listed under OSHA Hazards Communication Standards 29 CFR 1910.1200.

WHMIS Classification: Not a controlled product under WHMIS.

CERCLA: Not listed on CERCLA (40CFR 302.4). If this product is accidentally spilled, it is not subject to special reporting under requirements of the Comprehensive Environmental Response and Liability Act. We recommend you contact local authorities to determine if there may be other local reporting requirements.

SARA Title III Section 311/312: Under the provisions of Title III, Section 311/312 of the Superfund Amendments and Reauthorization Act, this product is classified into the following hazard category: **NONE**.

SARA Title III Section 313: This product does not contain more than 1 % of any of the chemical substances listed under SARA Section 313.

RCRA: Not listed on the **RCRA** (40 CFR 261.33) for hazardous waste.

NPRI: Not listed in the **NPRI** under Canadian EPA.

Chemical Inventory

Canada:	The ingredients of this product are on the DSL.
United States:	The ingredients of this product are on the TSCA



Please note: The identity of some or all of the ingredients is confidential and may be withheld as permitted.

SECTION XVI Other Information

HMIS Information

Degree of Hazard	HMIS Rating
4= Severe	Health 1
3= Serious	
2= Moderate	Flammability 1
1= Slight	
0= Minimal	Reactivity 0

Revision Information

Prepared by: Industrial Lubricants, LLC dba CAToil
Phone:480-515-1111

Effective Date: October 13, 2011

Supersedes: -

Revision: 0

Industrial Lubricants, LLC dba CAToil (the "Company"), shall not be liable for any damages arising from the information contained on this data sheet howsoever caused, if the product in question is not employed in a normal or foreseeable use or circumstances. The Company shall not be liable for any indirect or consequential damages arising out of the use of the information contained on this data sheet howsoever caused.