

MATERIAL SAFETY DATA SHEET 3M Super Weather strip and Gasket Adhesive -
Black, P.N. 08008 02/24/2008

3M

MATERIAL SAFETY DATA SHEET

Copyright, 2008, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3M Super Weather strip and Gasket Adhesive - Black, P.N.
08008

MANUFACTURER: 3M

DIVISION: Automotive Aftermarket

ADDRESS: 3M Center
St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 02/24/2008

Supercedes Date: 11/06/2006

Document Group: 08-0531-7

Product Use:

Intended Use: Automotive
Specific Use: Adhesive

SECTION 2: INGREDIENTS

Ingredient	C.A.S. No.	% by Wt
2-Chloro-1,3-Butadiene Polymers and Copolymers	Mixture	10 - 30
P-Tert-Butylphenol-Formaldehyde Resin	25085-50-1	10 - 30
Hexane, Other Isomers	Mixture	10 - 30
Methyl Ethyl Ketone	78-93-3	10 - 30
Hexane	110-54-3	5 - 15
Magnesium Oxide	1309-48-4	5 - 10
Toluene	108-88-3	5 - 10
Heptane, All Isomers	Mixture	1 - 7
Xylene	1330-20-7	0.5 - 5
Cyclopentane	287-92-3	< 1.5
Cyclohexane	110-82-7	< 1.5
Carbon Black	1333-86-4	0.1 - 1
Zinc Oxide	1314-13-2	< 1.0
Ethyl Benzene	100-41-4	<=0.272233
Talc	14807-96-6	<=0.1613
Benzene	71-43-2	<=0.033322
Formaldehyde	50-00-0	<=0.02918

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Odor, Color, Grade: Black: Solvent odor

General Physical Form: Liquid

Immediate health, physical, and environmental hazards: Flammable liquid and vapor.

Closed containers exposed to heat from fire may build pressure and explode.

Dust clouds of this material in combination with an ignition source may be explosive.

Vapors may travel long distances along the ground or floor to an ignition source and flash back. May cause allergic skin reaction. May cause severe skin irritation.

May cause target organ effects. Contains a chemical or chemicals which can cause birth defects or other reproductive harm. Contains a chemical or chemicals which can cause cancer.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact:

Severe Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Inhalation:

Intentional concentration and inhalation may be harmful or fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

May be absorbed following inhalation and cause target organ effects.

Ingestion:

Gastro intestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause:

Neurological Effects: Signs/symptoms may include personality changes, lack of Coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision.

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Peripheral Neuropathy: Signs/symptoms may include tingling or numbness of the extremities, in coordination, weakness of the hands and feet, tremors and muscle atrophy.

Olfactory effects: Signs/symptoms may include decreased ability to detect

odors and/ or complete loss of smell.

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	C.A.S. No.	Class Description	Regulation
Benzene	71-43-2	Group 1	International Agency for Research on Cancer
Benzene	71-43-2	Known human Carcinogen	National Toxicology Program Carcinogens
Benzene	71-43-2	Cancer hazard	OSHA Carcinogens
Carbon Black	1333-86-4	Group 2B	International Agency for Research on Cancer
Ethyl benzene	100-41-4	Group 2B	International Agency for Research on Cancer
Formaldehyde	50-00-0	Group 1	International Agency for Research on Cancer
Formaldehyde	50-00-0	Anticipated human Carcinogens	National Toxicology Program Carcinogen
Formaldehyde	50-00-0	Cancer hazard	OSHA Carcinogens

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel.

Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Auto ignition temperature	No Data Available
Flash Point	-6.00 degree F {Test Method: Tagliabue Closed Cup}
Flammable Limits - LEL	1.00 % volume
Flammable Limits - UEL	11.50 % volume

OSHA Flammability Classification: Class IB Flammable Liquid

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g. dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Closed containers exposed to heat from fire may build pressure and explode. Extremely flammable liquid and vapor. Dust clouds of this material in combination with an ignition source may be explosive. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill.

Evacuate unprotected and untrained personnel from hazard area.

The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools. Ventilate the area with fresh air. Contain spill. For larger spills, cover drains and build dikes to prevent entry into sewer systems of bodies of water. Cover spill area with a fire-extinguishing foam. An aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in insufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS.

Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Seal the container.

Dispose of collected material as soon as possible.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Avoid eye contact. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Ground containers securely when transferring contents. Wear low static or properly grounded shoes. Avoid breathing of vapors, mists or spray.

Avoid skin contact. Avoid static discharge. Avoid eye contact with vapors, mists, or spray. Keep out of the reach of children. Avoid contact with oxidizing agents.

7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Keep container in well- ventilated area. Keep container tightly closed. Store away from oxidizing agents.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Provide appropriate local exhaust ventilation on open containers. Do not use in a confined area or areas with little or no air movement.

Provide ventilation adequate to maintain dust concentration below minimum explosive concentrations.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields, Indirect Vented Goggles.

8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials. Gloves made from the following material(s) are recommended: Fluoroelastomer (Viton), Nitrile Rubber, Polyvinyl Alcohol (PVA).

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half face piece or full face air- purifying respirator with organic vapor cartridges and P95 particulate pre filters.

Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

Ingredient	Authority	Type	Limit	Additional Information
Benzene	ACGIH	TWA	0.5 ppm	Skin Notation*: Table A1
Benzene	ACGIH	STEL	2.5 ppm	Skin Notation*: Table A1
Benzene	OSHA	TWA	1 ppm	Standard Appendix
Benzene	OSHA	STEL	5 ppm	Standard Appendix
Carbon Black	ACGIH	TWA	3.5 mg/m ³	Table A4
Carbon Black	CMRG	TWA	0.5 mg/m ³	
Carbon Black	OSHA	TWA	3.5 mg/m ³	
Cyclohexane	ACGIH	TWA	100 ppm	
Cyclohexane	OSHA	TWA	300 ppm	Table Z-1
Cyclopentane	ACGIH	TWA	600 ppm	
Cyclopentane	OSHA	TWA	600 ppm	Table Z-1A
Ethyl benzene	ACGIH	TWA	100 ppm	Table A3
Ethyl benzene	ACGIH	STEL	125 ppm	Table A3
Ethyl benzene	OSHA	TWA	100 ppm	Table Z-1A
Ethyl benzene	OSHA	STEL	125 ppm	Table Z-1A
Formaldehyde	ACGIH	CEIL	0.3 ppm	Sensitizer: Table A2
Formaldehyde	OSHA	TWA	0.5 ppm	Standard Appendix
Hexane	ACGIH	TWA	50 ppm	Skin Notation*
Hexane	OSHA	TWA,	50 ppm	Table Z-1A
			Vacated	
Hexane	OSHA	TWA	500 ppm	Table Z-1A
Magnesium Oxide	ACGIH	TWA,	10 mg/m ³	Table A4
			As fume	
Magnesium Oxide	OSHA	TWA,	15 mg/m ³	Table Z-1
			As total dust	
Methyl Ethyl Ketone	ACGIH	TWA	200 ppm	
Methyl Ethyl Ketone	ACGIH	STEL	300 ppm	
Methyl Ethyl Ketone	OSHA	TWA	200 ppm	Table Z-1A
Methyl Ethyl Ketone	OSHA	STEL	300 ppm	Table Z-1A
Talc	ACGIH	TWA,	2 mg/m ³	Table A4
			Respirable	
Talc	CMRG	TWA,	0.5 mg/m ³	
			As respirable	
			Dust	

Talc	OSHA	TWA, 2 mg/m ³ Respirable	Table Z-1A
Toluene	ACGIH	TWA 20 ppm	Table A4
Toluene	CMRG	STEL 75 ppm	Skin Notation*
Toluene	OSHA	TWA, 100 ppm Vacated	
Toluene	OSHA	STEL, 150 ppm Vacated	
Toluene	OSHA	TWA 200 ppm	Table Z-2
Toluene	OSHA	CEIL 300 ppm	Table Z-2
Xylene	ACGIH	TWA 100 ppm	Table A4
Xylene	ACGIH	STEL 150 ppm	Table A4
Xylene	OSHA	TWA 100 ppm	Table Z-1A
Xylene	OSHA	STEL 150 ppm	Table Z-1A
Zinc Oxide	ACGIH	TWA, 2 mg/m ³ Respirable	
Zinc Oxide	ACGIH	STEL 10 mg/m ³	
Zinc Oxide	OSHA	TWA, 5 mg/m ³ As fume	Table Z-1
Zinc Oxide	OSHA	TWA, 5 mg/m ³ respirable	Table Z-1
Zinc Oxide	OSHA	STEL, 10 mg/m ³ Vacated, as fume	
Zinc Oxide	OSHA	TWA, 10 mg/m ³ Vacate, as dust	
Zinc Oxide	OSHA	TWA, 15 mg/m ³ As total dust	Table Z-1

. Substance(s) refer to the potential contribution to the overall exposure by the cutaneous Route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

VAC Vacated PEL: Vacated Permissible Exposure Limits {PEL} are enforced as the OSHA PEL in some states. Check with your local regulatory agency.

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Odor, Color, Grade:	Black: Solvent odor
General Physical Form:	Liquid
Auto ignition temperature:	No Data Available
Flash Point:	-6.00 degrees F {Test Method: Tagliabue Closed Cup}
Flammable Limits - LEL	1.00 % volume
Flammable Limits - UEL	11.50 % volume
Boiling Point	148 - 189 degrees F
Density	7.6 lb/gal
Vapor Density	3.00 {Ref Std: AIR=1}

Vapor Pressure 120.0000 mmHg {@ 68 degrees F}

Specific Gravity 0.90 {Ref Std: WATER=1}
pH Not Applicable

Melting Point No Data Available

Solubility in Water	Slight (less than 10%)
Evaporation rate	>=3.60 {Ref Std: ETHER=1}
Hazardous Air Pollutants	59.96 % weight
Volatile Organic Compounds	60.7 % weight {Test Method: calculated SCAQMD rule 443.1}
Percent volatile	60.7 % weight
VOC Less H2O & Exempt Solvents	546 g/l {Test Method: calculated SCAQMD rule 443.1}
Viscosity	7500.0 - 9500.0 centipoise

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable

Materials and Conditions To Avoid: Heat: Sparks and/or flames: Strong oxidizing agents

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Substance	Condition
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified
Toxic Vapor, Gas, Particulate	Not Specified

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information On this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in a permitted hazardous waste incinerator. As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.

Combustion products will include HCl. Facility must be capable of handling halogenated materials.

Dispose of empty product containers in a sanitary landfill.
Benzene concentration less than .0052%

EPA Hazardous Waste Number (RCRA): D001 (Ignitable), D035 (Methyl ethyl ketone)

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

ID Number(s): 41-3701-2175-2, 60-4550-2996-1, 60-9800-3122-7, LB-K000-1071-0

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS
Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No
Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient	C.A.S. No	% by Wt
Toluene	108-88-3	5 - 10
Xylene	1330-20-7	0.5 - 5
Hexane	110-54-3	5 - 15
Cyclohexane	110-82-7	< 1.5
Ethyl Benzene	100-41-4	<= 0.272233

This material contains a chemical which requires export notification under TSCA Section 12(b):

Ingredient (category if applicable)	C.A.S. No	Regulation	Status
Cyclohexane	110-82-7	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable

STATE REGULATIONS
Contact 3M for more information.

CALIFORNIA PROPOSITION 65

Ingredient	C.A.S. No.	Classification
Benzene	71-43-2	* Male reproductive toxin
Benzene	71-43-2	**Carcinogen
Benzene	71-43-2	*Developmental Toxin

Ethyl Benzene	100-41-4	**Carcinogen
Formaldehyde	50-00-0	**Carcinogen
Toluene	108-88-3	*Developmental Toxin

*WARNING: contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**WARNING: contains a chemical which can cause cancer.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

WHMIS: Hazardous

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 2 Flammability: 3 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:

Copyright was modified.

Section 3: Immediate physical hazard(s) was modified.

Section 3: Potential effects from skin contact information was modified.

Section 3: Potential effects from inhalation information was modified.

Section 5: unusual fire and explosion hazard information was modified.

Section 7: Handling information was modified.

Section 7: Storage information was modified.

Section 8: Respiratory protection information was modified.

Section 8: Respiratory protection-recommended respirators information was modified.

Section 3: Immediate other hazard(s) was modified.

Section 3: Other health effects information was modified.

Section 9: vapor pressure value was modified.

Section 9: Boiling point information was modified.

Sections 3 and 9: Odor, color, grade information was modified.

Section 9: Property description for optional properties was modified.
Section 3: Immediate skin hazard(s) was added.
Section 14: ID Number Heading Template 1 was added.
Section 14: ID Number(s) Template 1 was added.
Section 2: Ingredient table was added.
Section 15: TSCA section 12{b} text was added.
Section 15: EPCRA 313 information was added.
Section 15: EPCRA 313 text was added.
Section 8: Exposure guidelines ingredient information was added.
Section 8: Exposure guidelines legend was added.
Section 8: Exposure guideline note was added.
Section 15: TSCA section 12{b} information was added.
Section 8: Exposure guidelines data source legend was added.
Section 3: Carcinogenicity table was added.
Section 3: Carcinogenicity heading was added.
Section 15: California proposition 65 ingredient information was added.
Section 15: California proposition 65 heading was added.
Section 15: California proposition 65 cancer warning was added.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote Possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy.
In addition, information obtained from a database may not be as current as the information In the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com