



## **SAFETY DATA SHEET**

MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Version: 1.27

Revision Date: 02/06/2023

Print Date:  
04/07/2023

---

### **SECTION 1. IDENTIFICATION**

Product name : MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Product code : VV3246

#### **Manufacturer or supplier's details**

Company name of supplier : Valvoline LLC

Address : 100 Valvoline Way  
Lexington, KY 40509  
United States of America (USA)

Telephone : 1-800-TEAMVAL (1-800-832-6825)

E-mail address : SDS@valvoline.com

Emergency telephone : +1-800-VALVOLINE (+1-800-825-8654)  
number

#### **Recommended use of the chemical and restrictions on use**

Recommended use : Lubricant

---

### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Not a hazardous substance or mixture.

#### **GHS label elements**

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

#### **Other hazards**

None known.

---

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**



# SAFETY DATA SHEET

MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Version: 1.27

Revision Date: 02/06/2023

Print Date:  
04/07/2023

Substance / Mixture : Mixture

## Components

| Chemical name   | CAS-No.      | Concentration (% w/w) |
|---|--------------|-----------------------|
| Distillates (Petroleum), Hydrotreated Heavy Paraffinic  | 64742-54-7   | $\geq 70 - < 80$      |
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC  | 64742-54-7   | $\geq 10 - < 15$      |
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC  | 64742-54-7   | $\geq 1.5 - < 5$      |
| LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED   | 72623-86-0   | $\geq 1.5 - < 5$      |
| Short-, medium- and long-chain alkyl methacrylates and short-chain alkyl methacrylamide copolymer | Not Assigned | $\geq 1.5 - < 5$      |
| PETROLEUM DISTILLATES   | 64742-55-8   | $\geq 1 - < 1.5$      |
| distillates (petroleum), hydrotreated light paraffinic  | 64742-55-8   | $\geq 1 - < 1.5$      |

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

- General advice : Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : No symptoms known or expected.
- Notes to physician : Treat symptomatically.
- No hazards which require special first aid measures.



## SAFETY DATA SHEET

MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Version: 1.27

Revision Date: 02/06/2023

Print Date:  
04/07/2023

### SECTION 5. FIREFIGHTING MEASURES

- Hazardous combustion products : carbon dioxide and carbon monoxide
- Further information : Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).  
Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.
- Conditions for safe storage : Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : No materials to be especially mentioned.
- Further information on storage stability : No decomposition if stored and applied as directed.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

| Components | CAS-No. | Value type<br>(Form of exposure) | Control parameters / Permissible | Basis |
|------------|---------|----------------------------------|----------------------------------|-------|
|            |         |                                  |                                  |       |



## SAFETY DATA SHEET

MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Version: 1.27

Revision Date: 02/06/2023

Print Date:  
04/07/2023

|  |            |   | concentration |          |
|--|------------|---|---------------|----------|
| Distillates (Petroleum),<br>Hydrotreated Heavy Paraffinic    | 64742-54-7 | TWA (Mist)                                  | 5 mg/m3       | OSHA Z-1 |
|  |            | TWA<br>(Inhalable<br>particulate<br>matter) | 5 mg/m3       | ACGIH    |
| DISTILLATES (PETROLEUM),<br>HYDROTREATED HEAVY<br>PARAFFINIC | 64742-54-7 | TWA (Mist)                                  | 5 mg/m3       | OSHA Z-1 |
|  |            | TWA<br>(Inhalable<br>particulate<br>matter) | 5 mg/m3       | ACGIH    |
| DISTILLATES (PETROLEUM),<br>HYDROTREATED HEAVY<br>PARAFFINIC | 64742-54-7 | TWA (Mist)                                  | 5 mg/m3       | OSHA Z-1 |
|  |            | TWA<br>(Inhalable<br>particulate<br>matter) | 5 mg/m3       | ACGIH    |
| PETROLEUM DISTILLATES  | 64742-55-8 | TWA (Mist)                                  | 5 mg/m3       | OSHA Z-1 |
|  |            | TWA<br>(Inhalable<br>particulate<br>matter) | 5 mg/m3       | ACGIH    |
| distillates (petroleum),<br>hydrotreated light paraffinic    | 64742-55-8 | TWA (Mist)                                  | 5 mg/m3       | OSHA Z-1 |
|  |            | TWA<br>(Inhalable<br>particulate<br>matter) | 5 mg/m3       | ACGIH    |

### Personal protective equipment

Respiratory protection : Respiratory protection is not required under normal conditions of use.

No personal respiratory protective equipment normally required.

Eye protection : Safety glasses

Skin and body protection : Protective suit

Hygiene measures : General industrial hygiene practice.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid



## SAFETY DATA SHEET

MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Version: 1.27

Revision Date: 02/06/2023

Print Date:  
04/07/2023

|  |   |
|--|---|
| Colour   | : red   |
| Odour  | : mild  |
| Odour Threshold                                  | : No data available   |
| pH   | : No data available   |
| Melting point/freezing point                     | : No data available   |
| Boiling point/boiling range                      | : > 424 °F / 218 °C<br>(1013 hPa)                           |
| Flash point                                      | : 394 - 480 °F / 201 - 249 °C<br>Method: Cleveland open cup |
| Evaporation rate                                 | : < 1<br>Ethyl Ether  |
| Flammability (solid, gas)                        | : No data available   |
| Self-ignition                                    | : No data available   |
| Upper explosion limit / Upper flammability limit | : No data available   |
| Lower explosion limit / Lower flammability limit | : No data available   |
| Vapour pressure                                  | : 1 hPa<br>Calculated Vapor Pressure                        |
| Relative vapour density                          | : > 1<br>AIR=1  |
| Relative density                                 | : No data available   |
| Density  | : 0.837 g/cm <sup>3</sup> (60.01 °F / 15.56 °C)             |
| Solubility(ies)                                  |   |
| Water solubility                                 | : No data available   |
| Solubility in other solvents                     | : No data available   |
| Partition coefficient: n-                        | : No data available   |



# SAFETY DATA SHEET

MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Version: 1.27

Revision Date: 02/06/2023

Print Date:  
04/07/2023

octanol/water

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 28.8 mm<sup>2</sup>/s (104 °F / 40 °C)

Oxidizing properties : No data available

## SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : Stable under recommended storage conditions.  
No hazards to be specially mentioned.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Acute toxicity

Not classified based on available information.

### Components:

#### **Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg



## SAFETY DATA SHEET

MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Version: 1.27

Revision Date: 02/06/2023

Print Date:  
04/07/2023

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

### **LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute  
inhalation toxicity  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: No mortality observed at this dose.

### **distillates (petroleum), hydrotreated light paraffinic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute  
inhalation toxicity  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: No mortality observed at this dose.

### **Skin corrosion/irritation**

Not classified based on available information.

### **Components:**

#### **Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

### **LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:**



## SAFETY DATA SHEET

MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Version: 1.27

Revision Date: 02/06/2023

Print Date:  
04/07/2023

Species : Rabbit  
Result : No skin irritation

**distillates (petroleum), hydrotreated light paraffinic:**

Species : Rabbit  
Result : No skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Result : Slight, transient irritation  
Remarks : Expected based on components.

**Components:**

**Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**

Result : No eye irritation  
Assessment : No eye irritation

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Result : No eye irritation  
Assessment : No eye irritation

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Result : No eye irritation  
Assessment : No eye irritation

**LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:**

Species : Rabbit  
Result : No eye irritation

**Short-, medium- and long-chain alkyl methacrylates and short-chain alkyl methacrylamide copolymer:**

Result : Eye irritation

**distillates (petroleum), hydrotreated light paraffinic:**

Species : Rabbit  
Result : No eye irritation

**Respiratory or skin sensitisation**

**Skin sensitisation**

Not classified based on available information.





## SAFETY DATA SHEET

MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Version: 1.27

Revision Date: 02/06/2023

Print Date:  
04/07/2023

### Respiratory sensitisation

Not classified based on available information.

### Components:

#### LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:

|            |                                      |
|------------|--------------------------------------|
| Test Type  | : Buehler Test                       |
| Species    | : Guinea pig                         |
| Assessment | : Does not cause skin sensitisation. |

#### distillates (petroleum), hydrotreated light paraffinic:

|            |                                      |
|------------|--------------------------------------|
| Test Type  | : Buehler Test                       |
| Species    | : Guinea pig                         |
| Assessment | : Does not cause skin sensitisation. |

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Components:

#### Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

|                   |   |
|-------------------|---|
| Carcinogenicity - | : Classified based on DMSO extract content < 3% (Regulation |
| Assessment        | (EC) 1272/2008, Annex VI, Part 3, Note L)                   |

#### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

|                   |   |
|-------------------|---|
| Carcinogenicity - | : Classified based on DMSO extract content < 3% (Regulation |
| Assessment        | (EC) 1272/2008, Annex VI, Part 3, Note L)                   |

#### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

|                   |   |
|-------------------|---|
| Carcinogenicity - | : Classified based on DMSO extract content < 3% (Regulation |
| Assessment        | (EC) 1272/2008, Annex VI, Part 3, Note L)                   |

#### PETROLEUM DISTILLATES:

|                   |   |
|-------------------|---|
| Carcinogenicity - | : Classified based on DMSO extract content < 3% (Regulation |
| Assessment        | (EC) 1272/2008, Annex VI, Part 3, Note L)                   |

#### distillates (petroleum), hydrotreated light paraffinic:

|                   |   |
|-------------------|---|
| Carcinogenicity - | : Classified based on DMSO extract content < 3% (Regulation |
| Assessment        | (EC) 1272/2008, Annex VI, Part 3, Note L)                   |

### IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.



**SAFETY DATA SHEET**  
MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Version: 1.27

Revision Date: 02/06/2023

Print Date:  
04/07/2023

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Components:**

**Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**

May be fatal if swallowed and enters airways.

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

No aspiration toxicity classification

**LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

May be fatal if swallowed and enters airways.

**distillates (petroleum), hydrotreated light paraffinic:**

No aspiration toxicity classification

**Further information**

**Product:**

Remarks : No data available

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Product:**

**Ecotoxicology Assessment**



## SAFETY DATA SHEET

MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Version: 1.27

Revision Date: 02/06/2023

Print Date:  
04/07/2023

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

### **Components:**

#### **Distillates (Petroleum), Hydrotreated Heavy Paraffinic:**

Toxicity to fish : LL50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EL50 (Algae, algal mat (Algae)): > 100 mg/l  
plants Exposure time: 72 h

Toxicity to fish (Chronic : NOEC (Fish): 10 mg/l  
toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l  
aquatic invertebrates  
(Chronic toxicity)

#### **Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

##### **Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Toxicity to fish : LL50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EL50 (Algae, algal mat (Algae)): > 100 mg/l  
plants Exposure time: 72 h

Toxicity to fish (Chronic : NOEC (Fish): 10 mg/l  
toxicity)



## SAFETY DATA SHEET

MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Version: 1.27

Revision Date: 02/06/2023

Print Date:  
04/07/2023

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

### Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

### LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l  
Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l  
Exposure time: 21 d  
Test substance: WAF  
Method: OECD Test Guideline 211

### Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.



## SAFETY DATA SHEET

MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Version: 1.27

Revision Date: 02/06/2023

Print Date:  
04/07/2023

### Short-, medium- and long-chain alkyl methacrylates and short-chain alkyl methacrylamide copolymer:

#### Ecotoxicology Assessment

- Acute aquatic toxicity : Not classified based on available information.
- Chronic aquatic toxicity : Not classified based on available information.

### PETROLEUM DISTILLATES:

#### Ecotoxicology Assessment

- Acute aquatic toxicity : Not classified based on available information.
- Chronic aquatic toxicity : Not classified based on available information.

### distillates (petroleum), hydrotreated light paraffinic:

- Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l  
Exposure time: 14 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l  
Exposure time: 21 d  
Test substance: WAF  
Method: OECD Test Guideline 211

#### Ecotoxicology Assessment

- Acute aquatic toxicity : Not classified based on available information.



## SAFETY DATA SHEET

MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Version: 1.27

Revision Date: 02/06/2023

Print Date:  
04/07/2023

Chronic aquatic toxicity : Not classified based on available information.

### Persistence and degradability

#### Components:

##### **LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

##### **distillates (petroleum), hydrotreated light paraffinic:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

### Bioaccumulative potential

#### Components:

##### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Partition coefficient: n- : log Pow: Expected > 7  
octanol/water

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82  
Protection of Stratospheric Ozone - CAA Section 602 Class I  
Substances  
Remarks: This product neither contains, nor was  
manufactured with a Class I or Class II ODS as defined by the  
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +  
B).

Additional ecological : No data available  
information



## SAFETY DATA SHEET

MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Version: 1.27

Revision Date: 02/06/2023

Print Date:  
04/07/2023

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### 49 CFR

Not regulated as a dangerous good

#### Special precautions for user

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

---

### SECTION 15. REGULATORY INFORMATION

#### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : No SARA Hazards



# SAFETY DATA SHEET

MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Version: 1.27

Revision Date: 02/06/2023

Print Date:  
04/07/2023

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

## Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

## Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

## US State Regulations

### Massachusetts Right To Know

|  |            |
|--|------------|
| Distillates (Petroleum), Hydrotreated Heavy Paraffinic | 64742-54-7 |
| PETROLEUM DISTILLATES                                  | 64742-55-8 |
| distillates (petroleum), hydrotreated light paraffinic | 64742-55-8 |

### Pennsylvania Right To Know

|   |              |
|---|--------------|
| Distillates (Petroleum), Hydrotreated Heavy Paraffinic  | 64742-54-7   |
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC  | 64742-54-7   |
| PROPRIETARY COMPONENT OF HITEC 35300A - 000000278944  | Not Assigned |
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC  | 64742-54-7   |
| LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED   | 72623-86-0   |
| Short-, medium- and long-chain alkyl methacrylates and short-chain alkyl methacrylamide copolymer | Not Assigned |
| PETROLEUM DISTILLATES   | 64742-55-8   |
| distillates (petroleum), hydrotreated light paraffinic  | 64742-55-8   |

### Maine Chemicals of High Concern

|  |            |
|--|------------|
| Distillates (Petroleum), Hydrotreated Heavy Paraffinic | 64742-54-7 |
|--|------------|

### Vermont Chemicals of High Concern

|  |            |
|--|------------|
| Distillates (Petroleum), Hydrotreated Heavy Paraffinic | 64742-54-7 |
|--|------------|





# SAFETY DATA SHEET

MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Version: 1.27

Revision Date: 02/06/2023

Print Date:  
04/07/2023

## Washington Chemicals of High Concern

Distillates (Petroleum), Hydrotreated Heavy Paraffinic 64742-54-7

## California Permissible Exposure Limits for Chemical Contaminants

Distillates (Petroleum), Hydrotreated Heavy Paraffinic 64742-54-7

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY  
PARAFFINIC 64742-54-7

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY  
PARAFFINIC 64742-54-7

## The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AIIC : Not in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

TECI : On the inventory, or in compliance with the inventory

## TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

## Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

## SECTION 16. OTHER INFORMATION

### Further information



## SAFETY DATA SHEET


MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Version: 1.27

Revision Date: 02/06/2023

Print Date:  
04/07/2023

### NFPA 704:



### HMIS® IV:

|                 |   |   |
|-----------------|---|---|
| HEALTH          | / | 0 |
| FLAMMABILITY    |   | 1 |
| PHYSICAL HAZARD |   | 0 |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1  
Limits for Air Contaminants  
ACGIH / TWA : 8-hour, time-weighted average  
OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate;



## **SAFETY DATA SHEET**

MaxLife™ Full Synthetic Multi-Vehicle Automatic  
Transmission Fluid

Version: 1.27

Revision Date: 02/06/2023

Print Date:  
04/07/2023

NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 02/06/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Internal information : R0367943