

# SAFETY DATA SHEET

## PETROSOL 3139

000003000031



Version 3.1

Revision Date 2022/07/29

Print Date 2022/07/29

### SECTION 1. IDENTIFICATION

Product name : PETROSOL 3139  
Synonyms : Stoddard Solvent; Paint Thinner; Regular Mineral Spirits.  
Product code : S3139, S3139DRM

#### Manufacturer or supplier's details

Petro-Canada Lubricants Inc.  
2310 Lakeshore Road West  
Mississauga ON L5J 1K2  
Canada  
Telephone : 1-905-403-6785

#### Emergency telephone number

Emergency telephone number : CHEMTREC: 1-800-424-9300;  
Poison Control Centre: Consult local telephone directory for emergency number(s).

#### Recommended use of the chemical and restrictions on use

Recommended use : Petrosol 3139 is widely used in a variety of applications: thinning paints and varnishes; dissolving resins and plastics; diluent to formulate coatings, adhesives and printing inks; cleaning and degreasing metal and automotive parts; drycleaning solvent; floor and general household cleaner.

Prepared by : Product Safety: +1 905-491-0565

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 3  
Carcinogenicity : Category 2  
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)  
Aspiration hazard : Category 1

#### GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : Flammable liquid and vapour.  
May be fatal if swallowed and enters airways.  
May cause drowsiness or dizziness.  
Suspected of causing cancer.

# SAFETY DATA SHEET

## PETROSOL 3139

000003000031



Version 3.1

Revision Date 2022/07/29

Print Date 2022/07/29

Precautionary statements : **Prevention:**  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Keep container tightly closed.  
Ground and bond container and receiving equipment.  
Use explosion-proof electrical/ ventilating/ lighting equipment.  
Use non-sparking tools.  
Take action to prevent static discharges.  
Avoid breathing mist or vapours.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**  
IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
IF exposed or concerned: Get medical advice/ attention.  
Do NOT induce vomiting.  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

**Disposal:**  
Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

### IARC

Group 2B: Possibly carcinogenic to humans

ethylbenzene 100-41-4

naphthalene 91-20-3

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
stoddard solvent; Low boiling point naphtha — unspecified	8052-41-3	80 - 100
1,2,4-trimethylbenzene	95-63-6	1 - < 5
nonane	111-84-2	1 - < 5

# SAFETY DATA SHEET

## PETROSOL 3139

000003000031



Version 3.1

Revision Date 2022/07/29

Print Date 2022/07/29

xylene	1330-20-7	0.1 - < 1
ethylbenzene	100-41-4	0.1 - < 1
naphthalene	91-20-3	0.1 - < 1

Actual concentration or concentration range is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- If inhaled : Move to fresh air.  
Artificial respiration and/or oxygen may be necessary.  
Seek medical advice.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.  
Wash clothing before reuse.  
Seek medical advice.
- In case of eye contact : Remove contact lenses.  
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Obtain medical attention.
- If swallowed : Rinse mouth with water.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
Never give anything by mouth to an unconscious person.  
Seek medical advice.
- Most important symptoms and effects, both acute and delayed : First aider needs to protect himself.

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Dry chemical  
Carbon dioxide (CO<sub>2</sub>)  
Foam  
Water fog
- Unsuitable extinguishing media : Do NOT use water jet.
- Specific hazards during fire-fighting : Cool closed containers exposed to fire with water spray.
- Hazardous combustion products : Carbon oxides (CO, CO<sub>2</sub>), smoke and irritating vapours as products of incomplete combustion.
- Further information : Prevent fire extinguishing water from contaminating surface water or the ground water system.
- Special protective equipment : Wear self-contained breathing apparatus when fire fighting in

# SAFETY DATA SHEET

## PETROSOL 3139

000003000031



Version 3.1

Revision Date 2022/07/29

Print Date 2022/07/29

for firefighters

confined space.

Wear self-contained breathing apparatus and full protective wear.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Evacuate personnel to safe areas.  
Material can create slippery conditions.  
Mark the contaminated area with signs and prevent access to unauthorized personnel.  
Only qualified personnel equipped with suitable protective equipment may intervene.

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Methods and materials for containment and cleaning up : Prevent further leakage or spillage if safe to do so.  
Remove all sources of ignition.  
Soak up with inert absorbent material.  
Non-sparking tools should be used.  
Ensure adequate ventilation.  
Contact the proper local authorities.

---

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : None known.

Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin, eyes and clothing.  
Avoid inhalation of vapour or mist.  
Bonding and grounding alone may not be enough to dissipate static electricity that can cause fire or explosion.  
Do not ingest.  
Keep away from heat and sources of ignition.  
Keep container closed when not in use.  
Use only with adequate ventilation.

Conditions for safe storage : Store in original container.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Keep in a dry, cool and well-ventilated place.  
Keep in properly labelled containers.  
To maintain product quality, do not store in heat or direct sunlight.  
Ensure the storage containers are grounded/bonded.

# SAFETY DATA SHEET

## PETROSOL 3139

000003000031



Version 3.1

Revision Date 2022/07/29

Print Date 2022/07/29

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
stoddard solvent; Low boiling point naphtha — unspecified	8052-41-3	TWA	100 ppm 572 mg/m3	CA AB OEL
		TWA	290 mg/m3	CA BC OEL
		STEL	580 mg/m3	CA BC OEL
		TWAEV	100 ppm 525 mg/m3	CA QC OEL
		TWA	525 mg/m3	CA ON OEL
		TWA	100 ppm	ACGIH
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 123 mg/m3	CA AB OEL
		TWAEV	25 ppm	CA QC OEL
		TWA	25 ppm	CA BC OEL
		TWA	10 ppm	ACGIH
nonane	111-84-2	TWA	200 ppm 1,050 mg/m3	CA AB OEL
		TWAEV	200 ppm 1,050 mg/m3	CA QC OEL
		TWA	200 ppm	CA BC OEL
		TWA	200 ppm	ACGIH
xylene	1330-20-7	TWA	100 ppm 434 mg/m3	CA AB OEL
		STEL	150 ppm 651 mg/m3	CA AB OEL
		TWAEV	100 ppm 434 mg/m3	CA QC OEL
		STEV	150 ppm 651 mg/m3	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	20 ppm	ACGIH
ethylbenzene	100-41-4	STEL	125 ppm 543 mg/m3	CA AB OEL
		TWA	100 ppm 434 mg/m3	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		TWA	20 ppm	ACGIH
naphthalene	91-20-3	TWA	10 ppm 52 mg/m3	CA AB OEL
		STEL	15 ppm 79 mg/m3	CA AB OEL
		TWA	10 ppm	CA BC OEL
		TWAEV	10 ppm	CA QC OEL
		TWA	10 ppm	ACGIH

**Engineering measures** : Use only in well-ventilated areas.  
Use explosion-proof ventilation equipment.  
Adequate ventilation to ensure that Occupational Exposure

# SAFETY DATA SHEET

## PETROSOL 3139

000003000031



Version 3.1

Revision Date 2022/07/29

Print Date 2022/07/29

Limits are not exceeded.

### Personal protective equipment

- Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.  
Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Filter type : A NIOSH-approved air-purifying respirator with an organic vapour cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air-purifying respirators may not provide adequate protection.
- Hand protection  
Material : polyvinyl alcohol (PVA), Viton®. Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they should be changed.
- Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Protective measures : Wash contaminated clothing before re-use.
- Hygiene measures : Remove and wash contaminated clothing and gloves, including the inside, before re-use.  
Wash face, hands and any exposed skin thoroughly after handling.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : Clear and colourless
- Odour : Mild petroleum

# SAFETY DATA SHEET

## PETROSOL 3139

000003000031



Version 3.1

Revision Date 2022/07/29

Print Date 2022/07/29

Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	-76 °C (-105 °F)
Initial boiling point and boiling range	:	159 °C (318 °F)
Flash point	:	46 °C (115 °F) Method: Tag closed cup
Fire Point	:	No data available
Evaporation rate	:	0.1 (Butyl Acetate=1.0)
Flammability	:	Flammable, avoid open flames, sparks, static discharge and intense heat. Vapours are heavier than air and may travel considerable distance to sources of ignition and flash back. May accumulate in confined spaces.
Auto-Ignition Temperature	:	260 °C (500 °F)
Upper explosion limit / Upper flammability limit	:	6 %(V)
Lower explosion limit / Lower flammability limit	:	0.6 %(V)
Vapour pressure	:	0.285 kPa (20 °C / 68 °F)  0.9 kPa (38 °C / 100 °F)
Relative vapour density	:	4.8
Relative density	:	0.79
Density	:	No data available
Solubility(ies)		
Water solubility	:	negligible
Partition coefficient: n-octanol/water	:	No data available
Viscosity		
Viscosity, kinematic	:	1.21 cSt (25 °C / 77 °F)
Explosive properties	:	Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Containers may explode in heat of fire.

### SECTION 10. STABILITY AND REACTIVITY

# SAFETY DATA SHEET

## PETROSOL 3139

000003000031



Version 3.1

Revision Date 2022/07/29

Print Date 2022/07/29

Possibility of hazardous reactions	:	Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	Reactive with oxidising agents.
Hazardous decomposition products	:	May release CO <sub>x</sub> , smoke and irritating vapours when heated to decomposition.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Eye contact  
Ingestion  
Inhalation  
Skin contact

#### Acute toxicity

##### Product:

Acute oral toxicity	:	Remarks: No data available
Acute inhalation toxicity	:	Remarks: No data available
Acute dermal toxicity	:	Remarks: No data available

##### Components:

##### **stoddard solvent; Low boiling point naphtha — unspecified:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,
Acute inhalation toxicity	:	LC50 (Rat): > 5.5 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 (Rabbit): > 3,000 mg/kg,

##### **1,2,4-trimethylbenzene:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg,
Acute inhalation toxicity	:	LC50 (Rat): 18 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	:	LD50 (Rabbit): 3,160 mg/kg,

##### **xylene:**

Acute oral toxicity	:	LD50 (Rat): 4,300 mg/kg,
Acute inhalation toxicity	:	LC50 (Rat): 5000 ppm Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 (Rabbit): > 1,700 mg/kg,

# SAFETY DATA SHEET

## PETROSOL 3139

000003000031



Version 3.1

Revision Date 2022/07/29

Print Date 2022/07/29

### **ethylbenzene:**

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg,

Acute inhalation toxicity : LC50 (Rat): 4000 ppm  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 15,380 mg/kg,

### **naphthalene:**

Acute oral toxicity : LD50 (Rat): 490 mg/kg,

Acute dermal toxicity : LD50 (Rabbit): > 20,000 mg/kg,

### **Skin corrosion/irritation**

#### **Product:**

Remarks : No data available

### **Serious eye damage/eye irritation**

#### **Product:**

Remarks : No data available

### **Respiratory or skin sensitisation**

No data available

### **Germ cell mutagenicity**

#### **Product:**

Germ cell mutagenicity - Assessment : Animal testing did not show any mutagenic effects.

### **Carcinogenicity**

#### **Product:**

Carcinogenicity - Assessment : Suspected human carcinogens

Carcinogenicity - Assessment : Suspected human carcinogens

### **Reproductive toxicity**

#### **Product:**

Reproductive toxicity - Assessment : Animal testing did not show any effects on fertility.  
No toxicity to reproduction

### **STOT - single exposure**

#### **Product:**

Assessment : May cause drowsiness or dizziness.

# SAFETY DATA SHEET

## PETROSOL 3139

000003000031



Version 3.1

Revision Date 2022/07/29

Print Date 2022/07/29

### STOT - repeated exposure

**Product:**

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

**Product:**

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

### Persistence and degradability

**Product:**

Biodegradability : Remarks: No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Offer surplus and non-recyclable solutions to a licensed disposal company.  
Waste must be classified and labelled prior to recycling or disposal.  
Send to a licensed waste management company.  
Dispose of as hazardous waste in compliance with local and national regulations.  
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

# SAFETY DATA SHEET

## PETROSOL 3139

000003000031

Version 3.1

Revision Date 2022/07/29

Print Date 2022/07/29



### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

UN/ID No. : UN 1268  
Proper shipping name : Petroleum distillates, n.o.s.  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366

##### IMDG-Code

UN number : UN 1268  
Proper shipping name : PETROLEUM DISTILLATES, N.O.S.  
  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : yes

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

#### National Regulations

##### TDG

UN number : UN 1268  
Proper shipping name : PETROLEUM DISTILLATES, N.O.S.  
  
Class : 3  
Packing group : III  
Labels : 3  
ERG Code : 128  
Marine pollutant : yes

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Remarks : Special provisions: Please refer to TDGR Part 1.33 - Flammable Liquids: General Exemption

### SECTION 15. REGULATORY INFORMATION

#### The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

# SAFETY DATA SHEET

## PETROSOL 3139

000003000031

Version 3.1

Revision Date 2022/07/29

Print Date 2022/07/29



### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWA EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

For Copy of SDS : Internet: [lubricants.petro-canada.com/sds](http://lubricants.petro-canada.com/sds)  
Western Canada, telephone: 1-800-661-1199; fax: 1-800-378-4518

# SAFETY DATA SHEET

## PETROSOL 3139

000003000031



Version 3.1

Revision Date 2022/07/29

Print Date 2022/07/29

Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1-800-201-6285

Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285

For Product Safety Information: 1 905-491-0565

Prepared by : Product Safety: +1 905-491-0565

Revision Date : 2022/07/29  
Date format : yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN