

SECTION I. Chemical Product and Company Identification

Product Name/	Tom-Pac TP-2557 Bearing Gel	Code	
Trade Name		CAS#	mixture
Manufacturer	Tom-Pac Inc. 3571 Ashby St-Laurent, QC, H4R 2K3	In case of Emergency	514-332-4763
Synonym	Not Available		
Chemical Name	Not Applicable		
Chemical Family	Not Applicable		
Chemical Formula	mixture		
Material Uses	Lubrication for Industry		

SECTION II. Hazards Identification
SECTION II. Hazards Identification

This product is not classified as hazardous under harmonized GHS

Other known hazards: This product has not been found to pose any significant risk

Ratings:

Label elements:none

NFPA Hazard ID: Health:0

Flammability: 1

Reactivity: 0

HMIS Rating Health:0

Flammability: 1

Reactivity: 0

SECTION III. Composition and Information on Ingredients

Name	% by Weight
Synthetic base oil	75 - 85
Polytetrafluoroethylene	3
Inorganic thickener	8 - 12
Additives	6

SECTION IV. First Aid Measures

Eye Contact	Flush with plenty of water for at least 15 minutes. Seek medical attention if irritation develops
Skin Contact	Wash with soap and water. Hot material will burn on contact, cool contacted area.
Inhalation	Under normal conditions of use, this material is not expected to be an inhalation hazard. Allow victim to rest in well ventilated area
Ingestion	Do not induce vomiting. Seek medical attention

SECTION V. Fire Fighting Measures

Fire Fighting Media	Chemical Foam. Dry chemical or carbon dioxide
Inappropriate Media	Using water can cause oil fires to spread
Flammability of the Product	Oil based. Do not expose to flame. Product will burn.
Auto-Ignition Temperature	Not Available
Flash Points	approx 280°C COC
Products of Combustion	CO, CO2, NO, NO2, trace amounts of HF
Explosion Hazards in Presence of Various Substances	Not Available
Special Remarks on fire fighting	Evacuate area. Use protective fire gear in the case of large fires.
Special Remarks on Explosion Hazards	Drums exposed to intense heat could explode due to pressure buildup.

SECTION VI. Accidental Release Measures

Small Spill	Clean with mild solvent. Watch for slick surfaces Dispose or recycle according to local regulation for oil products
Large Spill	Do not allow to enter sewers or waterways, ground water Clean with mild solvent, absorb with an inert, non-combustible absorbent. Collect into container Dispose or recycle according to local regulation for oil products

SECTION VII. Handling and Storage

Storage	Keep away from sources of ignition. Keep container dry Keep container closed
Handling Procedures and Equipment	Use protective gloves. Use eye protection in areas where material has chance of throwing off of equipment

SECTION VIII. Exposure Controls Personal Protection

Engineering Controls	No special requirements, always have medical stations prepared, first aid and wash stations
Personal Protection	Use gloves to limit skin contact Eye Wear can be used to reduced risk of airborne material contacting eyes Respiartory protection is suggested when oil vapor/mist is above workplace safety limit protective clothing is not usually required unless cases of airborne heated material may be possible
TLV/PEL	None established Make certain working area has proper ventilation to control possible oil mist

SECTION IX. Physical and Chemical Properties	
Appearance	Pale yellow paste
Molecular Weight	Not applicable
pH(1% soln/water)	Not applicable
Boiling/Condensation Point	Not available
Melting/Sublimation Point	Not available
Specific Gravity	0.925
Density	Not available
Vapor Pressure	0.1 mm Hg at 20°C (estimated)
Vapor Density	Highest known value: <0.01 mm of Hg (@ 20°C)
Volatility	Not available
Odor/Odor Threshold	Not available
Evaporation Rate	0.01 compared to Butyl acetate
Viscosity	Not applicable
Water/Oil Dist. Coeff.	Not available
Solubility	Insoluble in cold water

SECTION X. Stability and Reactivity Data	
Stability	The product is stable
Instability Temperature	Not available
Conditions of Instability	Not available
Incompatibility with Various Substances	Strong acids & solvents will dissolve the product Contains hydrocarbons, not for oxygen use
Corrosivity	Not available
Special Remarks on Reactivity	avoid strong oxidizers

SECTION XI. Toxicological Information	
Routes of Entry	skin contact, ingestion
Toxicity to Animals	Oral LD50 (Rat) 5,000 mg/kg
Special Remarks on Toxicity to Animals	based on component testing
Acute Effects	
Eye Contact	Product is expected to be mild irritant
Skin Contact	Product is expected to be mild irritant (repeated contact)
Sensitization	Product is not expected to be a hazard
Ingestion	Product is expected to be slightly hazardous
Inhalation	Product is expected to be slightly hazardous
Remark	
Chronic Effects on Humans	No carcinogenic or mutagenic effects. Developmental / Reproductive Toxicity: Not available
Remarks	None

SECTION XII. Ecological Information	
Ecotoxicity	Not available
BOD5 and COD	Not available
Products of Biodegradation	short and long term products are not likely
Toxicity of the Products of Biodegradation	non-toxic
Special Remarks	None

SECTION XIII. Disposal Considerations	
Waste information	In accordance with provincial and federal regulations Contact regional environmental agency.

SECTION XIV. Transport Information	
TDG Road/Rail	Not controlled under TDC (Canada)
Remarks	Not regulated. Safe for air travel
Maritime Transportation	Not regulated. No special requirements

SECTION XV. Other Regulatory Information and Pictograms	
Federal & Provincial Regulations	Not controlled
WHMIS(Canada) Remark	Not a WHIMIS controlled material None
TSCA Status	listed or compliant
WHMIS(Canada)	Not a whimis controlled product

SECTION XVI. Other Information	
References	Not available
Other Special Considerations	Not available
Contact	Steve Katz, Systems Manager reviewed: May 2018
Notice to Reader Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material.	