



## Safety Data Sheet

Material Name: CALCINED MAGNESITE

SDS ID: CMC86505

### \*\*\*Section 1 - PRODUCT AND COMPANY IDENTIFICATION\*\*\*

Material Name: CALCINED MAGNESITE

#### Supplier Information

CMC Cometals  
2050 Center Avenue, Suite 250  
Fort Lee, NJ 07024  
Contact Phone #: (201) 302-0888

Emergency # CHEMTREC®: (800) 424-9300

#### Synonyms

DEADBURNED MAGNESITE

### \*\*\*Section 2 - HAZARDS IDENTIFICATION\*\*\*

#### POTENTIAL HEALTH EFFECTS

##### Inhalation

Short Term: irritation, changes in body temperature, nausea, vomiting, diarrhea, headache

Long Term: irritation, difficulty breathing

##### Skin

Short Term: irritation

Long Term: skin disorders

##### Eye

Short Term: irritation

Long Term: irritation

##### Ingestion

Short Term: irritation, nausea, vomiting, diarrhea, stomach pain, headache, drowsiness, dizziness, loss of coordination

Long Term: no information is available

### \*\*\*Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS\*\*\*

CAS	Component / EC#	Percent	Symbol(s)	Risk Phrase(s)
1309-48-4	MAGNESIUM OXIDE	>90.0	---	---
	215-171-9			

#### Component Related Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following: magnesium inorganic compounds.

#### Contaminants

May contain other metallic complexes.

### \*\*\*Section 4 - FIRST AID MEASURES\*\*\*

##### Inhalation

If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention.

##### Skin

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

# Safety Data Sheet

Material Name: CALCINED MAGNESITE

SDS ID: CMC86505

## Eyes

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

## Ingestion

If a large amount is swallowed, get medical attention.

## \*\*\*Section 5 - FIRE FIGHTING MEASURES\*\*\*

See Section 9 for Flammability Properties

NFPA Ratings: Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

## Flammable Properties

Negligible fire hazard.

## Extinguishing Media

Use extinguishing agents appropriate for surrounding fire.

## Fire Fighting Measures

Move container from fire area if it can be done without risk. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas.

## \*\*\*Section 6 - ACCIDENTAL RELEASE MEASURES\*\*\*

## Occupational spill/release

Collect spilled material in appropriate container for disposal.

## \*\*\*Section 7 - HANDLING AND STORAGE\*\*\*

## Storage Procedures

Store and handle in accordance with all current regulations and standards. Keep separated from incompatible substances.

## \*\*\*Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION\*\*\*

## Component Exposure Limits

### MAGNESIUM OXIDE (1309-48-4)

ACGIH: 10 mg/m3 TWA (inhalable fraction)

OSHA (US): 15 mg/m3 TWA (fume, total particulate)

OSHA (Vacated): 10 mg/m3 TWA (total particulate)

Mexico: 10 mg/m3 TWA LMPE (as Mg, fume)

## IDLH

750 mg/m3

## Ventilation

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

## PERSONAL PROTECTIVE EQUIPMENT

### Eyes/Face

Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

### Protective Clothing

Wear appropriate chemical resistant clothing.

### Glove Recommendations

Wear appropriate chemical resistant gloves.

### Respiratory Protection

Under conditions of frequent use or heavy exposure, respiratory protection may be needed.

Respiratory protection is ranked in order from minimum to maximum.

Consider warning properties before use.

150 mg/m3

# Safety Data Sheet

Material Name: CALCINED MAGNESITE

SDS ID: CMC86505

Any particulate respirator equipped with an N95, R95, or P95 filter (including N95, R95, and P95 filtering facepieces) except quarter-mask respirators. The following filters may also be used: N99, R99, P99, N100, R100 or P100.

Any supplied-air respirator.

375 mg/m3

Any supplied-air respirator operated in a continuous-flow mode.

Any powered, air-purifying respirator with a high-efficiency particulate filter.

750 mg/m3

Any air-purifying, full-facepiece respirator equipped with an N100, R100, or P100 filter.

Any powered, air-purifying respirator with a tight-fitting facepiece and a high-efficiency particulate filter.

Any self-contained breathing apparatus with a full facepiece.

Any supplied-air respirator with a full facepiece.

Emergency or planned entry into unknown concentrations or IDLH conditions -

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode.

Escape -

Any air-purifying, full-facepiece respirator equipped with an N100, R100, or P100 filter.

Any appropriate escape-type, self-contained breathing apparatus.

**For Unknown Concentrations or Immediately Dangerous to Life or Health -**

Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode.

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

## \* \* \*Section 9 - PHYSICAL AND CHEMICAL PROPERTIES\* \* \*

Physical State:	Solid	Appearance:	Not available
Physical Form:		Odor:	Not Available
Odor Threshold:	Not available	Melting Point:	Not available
Boiling Point:	Not applicable	Vapor Pressure:	Not applicable
Vapor Density (air = 1):	Not applicable	Density:	Not available
Specific Gravity (water = 1):	Not available	Water Solubility:	Not available
Coeff. Water/Oil Dist:	Not available		

## \* \* \*Section 10 - STABILITY AND REACTIVITY\* \* \*

### Chemical Stability

Stable at normal temperatures and pressure.

### Conditions to Avoid

None reported.

### Materials to Avoid

acids, metals, halogens, combustible materials

MAGNESIUM OXIDE:

ACIDS (STRONG): Violent reaction.

ALKALIS (STRONG): May attack.

ALUMINUM POWDER: May ignite or explode when heated.

BROMINE PENTAFLUORIDE: Violent reaction.

CHLORINE TRIFLUORIDE: May ignite.

INTERHALOGENS: Incompatible.

MAGNESIUM POWDER: May ignite or explode when heated.

# Safety Data Sheet

Material Name: CALCINED MAGNESITE

SDS ID: CMC86505

PHOSPHORUS PENTACHLORIDE: Incandesces brilliantly on heating.

SULFUR (SUBLIMED): May ignite or explode when heated.

## Decomposition Products

miscellaneous decomposition products

Thermal decomposition products: miscellaneous decomposition products.

## Possibility of Hazardous Reactions

Will not polymerize.

## \* \* \*Section 11 - TOXICOLOGICAL INFORMATION\* \* \*

### Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and no selected endpoints have been identified.

### RTECS Acute Toxicity (selected)

The components of this material have been reviewed and RTECS publishes no data as of the date on this document.

### RTECS Irritation

The components of this material have been reviewed and RTECS publishes no data as of the date on this document.

### Component Carcinogenicity

MAGNESIUM OXIDE (1309-48-4)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

### RTECS Tumorigenic

The components of this material have been reviewed, and RTECS publishes the following endpoints:

MAGNESIUM OXIDE (1309-48-4)

480 mg/kg Intratracheal Hamster TDLo (30 week)

### Medical Conditions Aggravated by Exposure

respiratory disorders, respiratory disorders, skin disorders, eye disorders

### Additional Data

Interactions with drugs may occur. Interactions with drugs may occur.

## HEALTH EFFECTS

### Inhalation - Toxicity Information

#### Inhalation Acute Exposure

MAGNESIUM OXIDE: The dust may cause respiratory tract irritation. Metal fume fever, an influenza-like illness, may occur if freshly formed magnesium oxide fumes composed of particles sized between 0.02-0.05 microns are inhaled in sufficient amounts. Symptoms may be delayed 4-12 hours and begin with a sudden onset of thirst, and a sweet, metallic or foul taste in the mouth. Other symptoms may include upper respiratory tract irritation accompanied by coughing and a dryness of the mucous membranes, lassitude and a generalized feeling of malaise. Fever, chills, muscular pain, mild to severe headache, nausea, occasional vomiting, exaggerated mental activity, profuse sweating, excessive urination, diarrhea, prostration and leukocytosis may also occur. Tolerance to fumes develops rapidly, but is quickly lost. All symptoms usually subside within 24-36 hours.

#### Inhalation Chronic Exposure

MAGNESIUM OXIDE: May cause respiratory tract irritation, nasal catarrh, and coughing up of discolored sputum. Dusts may cause chronic bronchitis, emphysema, and bronchial asthma.

### Skin Contact - Toxicity Information

#### Skin Contact Acute Exposure

MAGNESIUM OXIDE: Particulates may cause slight irritation.

#### Skin Contact Chronic Exposure

MAGNESIUM OXIDE: May cause eczema, edema, or hives.

# Safety Data Sheet

Material Name: CALCINED MAGNESITE

SDS ID: CMC86505

## Eye Contact - Toxicity Information

### Eye Contact Acute Exposure

MAGNESIUM OXIDE: May cause slight irritation, redness, and pain. Abrasive action of dust can damage eyes.

### Eye Contact Chronic Exposure

MAGNESIUM OXIDE: Repeated or prolonged exposure may cause conjunctivitis.

## Ingestion - Toxicity Information

### Ingestion Acute Exposure

MAGNESIUM OXIDE: Magnesium salts are generally so slowly absorbed that oral administration causes nothing more than purging. If evacuation fails, mucosal irritation and absorption may occur. If ingested in sufficient quantities, may cause gastrointestinal disturbances. Symptoms may include irritation, nausea, vomiting, abdominal pain, and diarrhea. Systemically, magnesium may produce central nervous system depression, abolition of reflexes, and death from respiratory paralysis.

### Ingestion Chronic Exposure

MAGNESIUM OXIDE: No data available.

## \*\*\*Section 12 - ECOLOGICAL INFORMATION\*\*\*

### Component Analysis - Aquatic Toxicity

No LOEL ecotoxicity data are available for this product's components.

## \*\*\*Section 13 - DISPOSAL CONSIDERATIONS\*\*\*

### Disposal Methods

Dispose in accordance with all applicable regulations.

### Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

## \*\*\*Section 14 - TRANSPORT INFORMATION\*\*\*

### US DOT Information

No Classification assigned.

### TDG Information

No Classification assigned.

### ADR Information

No Classification assigned.

### RID Information

No Classification assigned.

### IATA Information

No Classification assigned.

### ICAO Information

No Classification assigned.

### IMDG Information

No Classification assigned.

## \*\*\*Section 15 - REGULATORY INFORMATION\*\*\*

### U.S. Federal Regulations

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes Chronic Health: No Fire: No Pressure: No Reactive: No

# Safety Data Sheet

Material Name: CALCINED MAGNESITE

SDS ID: CMC86505

## U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
MAGNESIUM OXIDE	1309-48-4	Yes	Yes	Yes	Yes	Yes

Not regulated under California Proposition 65

## Canada WHMIS

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

**MAGNESIUM OXIDE (1309-48-4)**

1 %

## Germany Water Classification

**MAGNESIUM OXIDE (1309-48-4)**

Annex 3: ID Number 5208, hazard class 1 - low hazard to waters

## Safety Phrases

None required.

## Component Analysis - Inventory

Component	CAS	US	CA	EU	AU	PH	JP	KR	CN	NZ
MAGNESIUM OXIDE	1309-48-4	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes

## \* \* \*Section 16 - OTHER INFORMATION\* \* \*

### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RID - European Rail Transport; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States

### Other Information

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. **Disclaimer:** Supplier gives no warranty of merchantability or of fitness for a particular purpose. Any product purchased is sold on the assumption the purchaser will make his own tests to determine the quality and suitability of the product. Supplier expressly disclaims any and all liability for incidental and/or consequential property damage arising out of the use of this product. No information provided shall be deemed to be a recommendation to use any product in conflict with any existing patent rights. Read the Material Safety Data Sheet before handling product.

## Safety Data Sheet

Material Name: CALCINED MAGNESITE

SDS ID: CMC86505

"RTECS®" is a United States trademark owned and licensed under authority of the U.S. Government, by and through Accelrys, Inc. Portions ©Copyright 2011, U.S. Government. All rights reserved.

End of Sheet CMC86505