

# Material Safety Data Sheet



Zep Inc.  
1310 Seaboard Industrial Blvd.  
Atlanta, GA 30318  
1-877-I-BUY-ZEP (428-9937)  
www.zep.com

## Section 1. Chemical Product and Company Identification

**Product name** HIGH PH PRESOAK (XT-1398)  
**Product use** Liquid Vehicle Wash  
**Product code** 9885  
**Date of issue** 01/21/09      **Supersedes** 11/11/05

## Emergency Telephone Numbers

**For MSDS Information:**  
Compliance Services 1-877-I-BUY-ZEP (428-9937)

**For Medical Emergency**  
(877) 541-2016 Toll Free - All Calls Recorded

**For Transportation Emergency**  
CHEMTREC: (800) 424-9300 - All Calls Recorded  
In the District of Columbia (202) 483-7616

## Prepared By

Compliance Services  
1420 Seaboard Industrial Blvd.  
Atlanta, GA 30318

Printing date: 01/22/09

## Section 2. Hazards Identification

### Emergency overview

\*Hazard Determination System (HDS): Health, Flammability, Reactivity

DANGER !

3    0    0

CAUSES EYE BURNS. CAUSES SKIN IRRITATION. MAY BE HARMFUL IF ABSORBED THROUGH SKIN. HARMFUL IF SWALLOWED.

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

### Acute Effects

### Routes of Entry

Dermal contact. Eye contact. Inhalation. Ingestion.

#### Eyes

Causes eye burns. Eye exposure may cause severe and permanent eye injury (blindness).

#### Skin

Causes skin irritation. Skin inflammation is characterized by itching, scaling, reddening or, occasionally, blistering. Prolonged contact can cause severe irritation or even burns. May be harmful if absorbed through the skin.

#### Inhalation

Avoid breathing vapors, spray or mists. Over-exposure by inhalation may cause respiratory irritation. Can cause central nervous system (CNS) depression.

#### Ingestion

Harmful if swallowed. May cause burns to mouth, throat and stomach.

### Chronic effects

Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to spray or mist may produce respiratory tract irritation, leading to frequent attacks of bronchial infection. Contains material which may cause damage to the following organs: blood, kidneys, lungs, liver.

### Carcinogenicity

Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

Additional Information: See Toxicological Information (Section 11)

## Section 3. Composition/Information on Ingredients

SODIUM METASILICATE; silicic acid (H2-Si-O3) disodium salt; water glass	6834-92-0	1 - 10
PROPRIETARY SOLVENT BLEND	Proprietary	5 - 15
TETRASODIUM ETHYLENEDIAMINE TETRAACETATE; ethylenediamine tetraacetic acid; tetrasodium salt	64-02-8	1 - 10
ALCOHOLS, C9-11, ETHOXYLATED; linear primary alcohol ethoxylate	68439-46-3	1 - 10

## Section 4. First Aid Measures

<b>Eye Contact</b>	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.
<b>Skin Contact</b>	Flush affected skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if irritation develops.
<b>Inhalation</b>	Move exposed person to fresh air. If irritation persists, get medical attention.
<b>Ingestion</b>	Do not induce vomiting unless directed to do so by medical personnel. If affected person is conscious, give plenty of water to drink. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Section 5. Fire Fighting Measures**

National Fire Protection Association (U.S.A.)

**Flash Point** None.**Flammable Limits** Not available.**Flammability** Non-combustible.**Fire hazard** In a fire or if heated, a pressure increase will occur and the container may burst.**Fire-Fighting Procedures** Use an extinguishing agent suitable for the surrounding fire.**Section 6. Accidental Release Measures**

**Spill Clean up** Put on appropriate personal protective equipment (see section 8). Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Section 7. Handling and Storage**

**Handling** Put on appropriate personal protective equipment (see section 8). Do not get in eyes, on skin or on clothing. Avoid breathing vapors, spray or mists. Do not ingest. Do not reuse container. Observe label precautions. Wash thoroughly after handling.

**Storage** Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Store between the following temperatures: 40°F - 120°F (4.4°C - 49°C). Keep out of the reach of children.

**Section 8. Exposure Controls/Personal Protection****Product name**

PROPRIETARY SOLVENT BLEND

**Exposure limits**

OSHA PEL (United States).

TWA: 500 ppm 8 hour(s).

ACGIH TLV (United States).

TWA: 50 ppm 8 hour(s).

SODIUM METASILICATE; silicic acid (H<sub>2</sub>-Si-O<sub>3</sub>) disodium salt; water glass

ACGIH TLV (United States).

TWA: 10 mg/m<sup>3</sup> 8 hour(s). Form: Dust

OSHA PEL (United States).

: 15 mg/m<sup>3</sup> Form: Dust**Personal Protective Equipment (PPE)****Eyes** Splash goggles. Face shield.**Body** Wear appropriate protective clothing to prevent skin contact. Recommended: Neoprene gloves. Nitrile gloves. Rubber gloves. Wear apron or coverall if there is a risk of exposure to splashes. Chemical resistant boots.**Respiratory** Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Wear appropriate respirator when ventilation is inadequate.**Section 9. Physical and Chemical Properties****Physical State** Liquid.**Color** Clear. Amber. [Light]**pH** 13.0 - 13.5**Odor** Mild.**Boiling Point** 100°C (212°F)**Vapor Pressure** Not determined.**Specific Gravity** 1.1**Vapor Density** Not determined.**Solubility** Easily soluble in the following materials: cold water and hot water.**Evaporation Rate** 1 (Water = 1)**VOC (Consumer)** 8.52% 0.78 (lb/gal) 93 (g/l).**Section 10. Stability and Reactivity****Stability and Reactivity** The product is stable.**Incompatibility** Reactive or incompatible with the following materials: oxidizing materials and acids.**Hazardous Polymerization** Will not occur.**Hazardous Decomposition Products** carbon oxides (CO, CO<sub>2</sub>), nitrogen oxides (NO, NO<sub>2</sub> etc.)

**Section 11. Toxicological Information****Acute Toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Sodium Metasilicate	LD50 Oral	Rat	2200 mg/kg	-
Tetrasodium Ethylenediamine Tetraacetate	LD50 Oral	Rat	4100 mg/kg	-
Ethoxylated Alcohols	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	1400 mg/kg	-

**Section 12. Ecological Information**

**Environmental Effects** No known significant effects or critical hazards.

**Aquatic Ecotoxicity**

Not available.

**Section 13. Disposal Considerations****Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

**Waste Stream** Code: D002

Classification: - [Hazardous waste]

Origin: - [RCRA waste.]

**Section 14. Transport Information**

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
<b>DOT Classification</b>	3266	Corrosive liquid, basic, inorganic, n.o.s. (Sodium Metasilicate)	8	II	
<b>IMDG Class</b>	Not determined.				

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG\* : Packing group

**Section 15. Regulatory Information****U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

**Product name**

Glycol Ethers

**Clean Water Act (CWA) 307:** No products were found.

**Clean Water Act (CWA) 311:** No products were found.

**Clean Air Act (CAA) 112 regulated toxic substances:** No products were found.

All Components of this product are listed or exempt from listing on TSCA Inventory.

**State Regulations****California Prop 65**

No products were found.

**Section 16. Other Information**

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.*

*Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*

\*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.